

LIVERMORE AMADOR VALLEY TRANSIT AUTHORITY DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT

JANUARY 2017

Kimley»Horn

© 2017 KIMLEY-HORN AND ASSOCIATES, INC.
4637 CHABOT DR., SUITE 300, PLEASANTON, CA 94588
PHONE: 925-398-4840
WWW.KIMLEY-HORN.COM



JANUARY 2017

ISSUES/REVISIONS

NO. DATE DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT


PROJECT NUMBER: 097026201
SCALE: SEE PLAN

TITLE SHEET

CV-01

1 OF 26

SHEET INDEX	
SHEET	DESCRIPTION
1	CV-01 Title Sheet
2	NT-01 Traffic Signal General Notes
3	DT-01 Traffic Signal Details
4	DT-02 Traffic Signal Details
5	TS-01 Dublin Blvd & San Ramon Rd
6	TS-02 Dublin Blvd & Regional St
7	TS-03 Dublin Blvd & Golden Gate Dr
8	TS-04 Dublin Blvd & Amador Valley Rd
9	TS-05 Dublin Blvd & Village Pkwy
10	TS-06 Dublin Blvd & Village Pkwy Schedule
11	TS-07 Dublin Blvd & Clark Ave
12	TS-08 Dublin Blvd & Sierra Ct
13	TS-09 Dublin Blvd & Dublin Ct
14	TS-10 Dublin Blvd & Dougherty Rd
15	TS-11 Dublin Blvd & Scarlett Dr
16	TS-12 Dublin Blvd & DeMarcus Blvd
17	TS-13 Dublin Blvd & Iron Horse Pkwy
18	TS-14 Dublin Blvd & Arnold Rd
19	TS-15 Dublin Blvd & Arnold Rd Schedules
20	TS-16 Dublin Blvd & Persimmon
21	TS-17 Dublin Blvd & Hacienda Dr
22	TS-18 Hacienda Dr & Martinelli Wy
23	TS-19 Dublin Blvd & Tassajara Road
24	TS-20 Dublin Blvd & Tassajara Road Schedule
25	SS-01 Dublin Blvd & Village, Arnold
26	SS-02 Dublin Blvd & Tassajara Rd



LOCATION MAP
NOT TO SCALE

- VEHICLE DETECTION MODIFICATION
- VEHICLE AND BICYCLE DETECTION MODIFICATION
- VEHICLE AND BICYCLE DETECTION MODIFICATION, INSTALLATION OF Q-JUMP
- INSTALLATION OF Q-JUMP

APPROVAL OF THESE PLANS DOES NOT RELEASE THE CONTRACTOR OF THE RESPONSIBILITY FOR CORRECTION OF MISTAKES, ERRORS, OR OMISSIONS CONTAINED THEREIN. IF DURING THE COURSE OF CONSTRUCTION OF THE IMPROVEMENTS PUBLIC INTEREST REQUIRES A MODIFICATION OF OR A DEPARTURE FROM THE SPECIFICATIONS AND DETAILS OF THE CITY OF LIVERMORE OR THESE PLANS, THE ENGINEER SHALL HAVE THE AUTHORITY TO REQUIRE SUCH MODIFICATIONS OR DEPARTURE AND TO SPECIFY THE MANNER IN WHICH SAME IS TO BE MADE.

APPROVED AS TO DESIGN ONLY BASED ON INFORMATION SUBMITTED HEREON.

APPROVED FOR THE LIVERMORE AMADOR VALLEY TRANSIT AUTHORITY:

BY: *Michael Tree* 1/23/2017
MICHAEL TREE DATE
EXECUTIVE DIRECTOR

CITY OF DUBLIN PUBLIC WORKS RECOMMENDED FOR APPROVAL

BY: *Andrew Russell* 1/23/2017
ANDREW RUSSELL, P.E. DATE
CITY ENGINEER

KIMLEY-HORN AND ASSOCIATES, INC.
PREPARED UNDER THE DIRECTION OF:

Nikita Petrov 01/20/17
NIKITA A. PETROV DATE
R.C.E. 80570 EXPIRES 03/31/17

OWNER
LIVERMORE AMADOR VALLEY TRANSIT AUTHORITY
1362 RUTAN COURT, SUITE 100
LIVERMORE, CA 94551
PHONE: (925) 455-7555
CONTACT: SILVIA COX

CIVIL ENGINEER
KIMLEY-HORN AND ASSOCIATES, INC.
4637 CHABOT DRIVE, SUITE 300
PLEASANTON, CA 94588
PHONE: (925) 398-4840
CONTACT: NIKITA PETROV

CITY OF DUBLIN
ENGINEERING DIVISION, TRAFFIC ENGINEER
100 CIVIL PLAZA
DUBLIN, CA 94568
PHONE: (925) 833-6630
CONTACT: WILLIAM LAI

PROJECT GENERAL NOTES:

- 1. THE CONTRACTOR AGREES THAT, IN ACCORDANCE WITH GENERALLY ACCEPTED CONSTRUCTION PRACTICES, THE CONTRACTOR SHALL BE REQUIRED TO ASSUME SOLE AND COMPLETE RESPONSIBILITY FOR JOB SITE CONDITIONS DURING THE COURSE OF CONSTRUCTION OF THE PROJECT, INCLUDING SAFETY OF ALL PERSONS AND PROPERTY. THIS REQUIREMENT SHALL BE MADE TO APPLY CONTINUOUSLY AND NOT BE LIMITED TO NORMAL WORKING HOURS.
- 2. THE CONTRACTOR SHALL POST EMERGENCY TELEPHONE NUMBERS FOR POLICE, FIRE, AMBULANCE, AND THOSE AGENCIES RESPONSIBLE FOR MAINTENANCE OF UTILITIES IN THE VICINITY OF JOB SITE.
- 3. THE GENERAL CONTRACTOR IS RESPONSIBLE FOR COORDINATING ALL OF THE WORK PERFORMED BY HIS SUBCONTRACTORS WITHOUT EXCEPTION.
- 4. THE CONTRACTOR SHALL IDENTIFY A RESPONSIBLE CONTACT PERSON, WHO IS AN EMPLOYEE OF THE CONTRACTOR, AND A 24-HOUR TELEPHONE NUMBER TO CALL TO RESOLVE PROBLEMS WITH NOISE, DUST OR OTHER CONSTRUCTION RELATED ISSUES.
- 5. THE CONTRACTOR SHALL BE REQUIRED TO KEEP ALL CONSTRUCTION ACTIVITIES WITHIN THE RIGHTS-OF-WAY AND EASEMENTS OBTAINED FOR THIS PROJECT UNLESS OTHERWISE SHOWN. THIS SHALL INCLUDE, BUT NOT BE LIMITED TO, VEHICLES AND EQUIPMENT, LIMITS OF TRENCH EXCAVATIONS, AND STOCKPILED NEW MATERIAL.
- 6. THE CONTRACTOR SHALL PROVIDE PROTECTIVE DEVICES INCLUDING BARRICADES, FENCING, WARNING SIGNS, LIGHTS, FLAGGERS OR OTHER ITEMS NECESSARY TO ENSURE PUBLIC SAFETY WITHIN THE PROJECT SITE. THIS REQUIREMENT SHALL APPLY CONTINUOUSLY AND NOT BE LIMITED TO NORMAL WORKING HOURS.
- 7. EXISTING CITY COMMUNICATION AND SIGNAL FACILITIES ARE LOCATED IN THE PROJECT AREA. COMMUNICATION AND SIGNAL FACILITIES DAMAGED BY CONTRACTOR'S OPERATIONS SHALL BE TEMPORARILY REPAIRED AND THEN REPLACED AT THE CONTRACTOR'S EXPENSE. DAMAGED SIGNAL INTERCONNECT CABLE SHALL BE REPLACED FOR THE ENTIRE LENGTH BETWEEN CONTROLLER CABINETS.
- 8. CONTRACTOR SHALL EXERCISE DUE CAUTION DURING CONSTRUCTION TO PROTECT ANY EXISTING LANDSCAPING, FIXTURES, EQUIPMENT, IRRIGATION, CONCRETE SIDEWALK, CONCRETE DRIVEWAY, CONCRETE CURB AND GUTTER, AND AC PAVING TO REMAIN. ANY DAMAGE RESULTING FROM CONTRACTOR OPERATIONS SHALL BE REPAIRED AS DIRECTED BY THE CITY'S REPRESENTATIVE, AT NO ADDITIONAL COST TO THE CITY.
- 9. DUST SHALL BE CONTROLLED AND ADJOINING STREET AND PRIVATE DRIVEWAYS SHALL BE KEPT CLEAN OF PROJECT DIRT, MUD, MATERIALS AND DEBRIS, TO THE SATISFACTION OF THE COUNTY ENGINEER.
- 10. THIS PROJECT INVOLVES WORK IN PUBLIC AREAS AND NEAR PRIVATE PROPERTY. THE CONTRACTOR SHALL SPECIFICALLY INSTRUCT ALL HIS/HER WORKERS TO EXERCISE GOOD PUBLIC RELATIONS DURING THE WORK, INCLUDING BEING COURTEOUS, AVOIDING THE USE OF SWEAR WORDS, AND MINIMIZING DAMAGE TO EXISTING IMPROVEMENTS.
- 11. CONTRACTOR SHALL SWEEP AND CLEAN THE CONSTRUCTION SITE DAILY BEFORE THE END OF EACH WORKING DAY.
- 12. IT IS INTENDED THAT THESE PLANS REQUIRE ALL LABOR AND MATERIALS NECESSARY FOR COMPLETION OF WORK IN ACCORDANCE WITH THEIR TRUE INTENT AND PURPOSE. CONTRACTOR SHALL NOTIFY ENGINEER IMMEDIATELY REGARDING ANY DISCREPANCIES OR AMBIGUITIES WHICH MAY EXIST IN PLANS OR SPECIFICATIONS. ENGINEER'S INTERPRETATION OR CORRECTION THEREOF SHALL BE FINAL AND CONCLUSIVE. WHERE PLANS OR SPECIFICATIONS DESCRIBE PORTIONS OF WORK IN GENERAL TERMS BUT NOT IN COMPLETE DETAIL, IT IS UNDERSTOOD THAT THE ENGINEER SHALL DETERMINE THE BEST GENERAL PRACTICE TO BE USED AND ONLY MATERIALS AND WORKMANSHIP OF FIRST QUALITY SHALL BE USED.
- 13. THE CONTRACTOR SHALL NOTIFY THE CITY'S REPRESENTATIVE IMMEDIATELY, UPON DISCOVERY OF ANY POTENTIAL FIELD CONFLICTS.
- 14. PROPER TRAFFIC CONTROL SHALL BE MAINTAINED AT ALL TIMES DURING CONSTRUCTION IN ACCORDANCE WITH THE 2014 CALIFORNIA MUTCD. CONTRACTOR SHALL SUBMIT TRAFFIC CONTROL PLANS TO CITY FOR REVIEW AT PRE-CONSTRUCTION MEETING BEFORE STARTING ANY WORK. CONTRACTOR SHALL MAINTAIN PEDESTRIAN ACCESS AT ALL TIMES.
- 15. CONTRACTOR SHALL SEQUENCE WORK TO MAINTAIN PEDESTRIAN ACCESS AROUND EACH INTERSECTION AT ALL TIMES.

UTILITY NOTES:

- 1. ALL EXISTING UTILITY LOCATIONS ARE APPROXIMATE. CONTRACTOR SHALL TAKE ALL PRECAUTIONARY MEASURES TO PROTECT THESE UTILITIES. CONTRACTOR SHALL NOT PERFORM ANY EXCAVATION UNTIL ALL UTILITY AGENCIES HAVE BEEN NOTIFIED AND HAVE BEEN GIVEN THE OPPORTUNITY TO MARK THEIR UNDERGROUND FACILITIES IN THE FIELD. CONTRACTOR SHALL CALL U.S.A. (800) 227-2600 AT LEAST 2 WORKING DAYS IN ADVANCE OF THE START OF CONSTRUCTION OF THE PROJECT. CONTRACTOR SHALL POTHOLE AND DETERMINE THE DEPTH OF ALL UTILITIES PRIOR TO CONSTRUCTION.
- 2. CONTRACTOR SHALL LOCATE AND PRESERVE ALL FACILITIES INCLUDING SEWER, WATER, GAS, IRRIGATION, POWER, STREET LIGHTS, TELEPHONE, SURVEY MARKERS AND OTHERS WHICH MAY BE IN AREA OF CONSTRUCTION, PRIOR TO INSTALLATION OF SIGNAL POLES. NOT ALL LATERALS ARE SHOWN ON THE PLANS. THE CONTRACTOR SHALL LOCATE AND MARK LATERALS PRIOR TO CONSTRUCTION.
- 3. CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING ADJUSTMENT OF ALL EXISTING UTILITIES WITH THE RESPECTIVE UTILITY COMPANIES AT NO ADDITIONAL COST.
- 4. CONTRACTOR SHALL MAINTAIN ALL EXISTING SEWER AND WATER SERVICE TO PROPERTIES WITHIN CONSTRUCTION AREA AT ALL TIMES DURING CONSTRUCTION.

TRAFFIC SIGNAL GENERAL NOTES:

- 1. ALL WORK AND MATERIALS SHALL COMPLY WITH THE 2015 STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION (CALTRANS) REVISED STANDARD PLANS AND CALTRANS REVISED STANDARD SPECIFICATIONS.
- 2. ALL SIGN CODES REFER TO THE 2014 CALIFORNIA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (CAMUTCD) UNLESS OTHERWISE NOTED.
- 3. REFER TO CALTRANS REVISED STANDARD PLANS ES-IA, ES-IB, AND ES-1C FOR KEY TO SYMBOLS AND ABBREVIATIONS.
- 4. ALL NEW PULL BOXES SHALL BE #5 UNLESS OTHERWISE NOTED ON THE PLANS.
- 5. ALL SIGNAL POLES AND SIGNAL STANDARDS SHALL BE GALVANIZED.
- 6. ALL NEW SIGNAL EQUIPMENT SHALL BE FURNISHED AND INSTALLED BY THE CONTRACTOR AS SPECIFIED ON THESE PLANS AND SPECIAL PROVISIONS.
- 7. TRAFFIC SIGNAL POLES SHALL BE SET BACK FROM FACE OF CURB NO LESS THAN 30 INCHES TO FACE OF STANDARD OR POLE, AND THE BASE PLATE INSTALLED PARALLEL TO THE STOP BAR UNLESS OTHERWISE SPECIFIED BY THE ENGINEER.
- 8. CONTRACTOR SHALL PROTECT ALL EXISTING CABLES AND CONDUCTORS INSIDE EXISTING CONDUITS AND PULL BOXES WHERE NEW CABLES ARE TO BE INSTALLED.
- 9. AS-BUILTS USED ON THIS PROJECT MAY NOT REPRESENT ALL RECENT CHANGES. FIELD VERIFICATION IS RECOMMENDED.
- 10. ALL NEW ETHERNET CABLES AND EXTENDERS CONNECTED TO MICROWAVE DETECTORS SHALL BE LABELED WITH THE PHASE NUMBERS CORRESPONDING TO THE MICROWAVE DETECTOR.
- 11. AS BUILTS USED ON THIS PROJECT ARE SHOWN FOR REFERENCE PURPOSES ONLY TO IDENTIFY LOCATION OF EXISTING SIGNAL EQUIPMENT. ALL CONSTRUCTION NOTES AND GENERAL NOTES ASSOCIATED WITH THESE AS BUILTS SHALL NOT BE TAKEN IN CONSIDERATION. CONTRACTOR SHALL VERIFY WITH ENGINEER FOR CLARIFICATION IF CONFLICT IS DISCOVERED.

LEGEND

PROPOSED	EXISTING
	CONDUIT
	CURB
	EDGE OF PAVEMENT
	SIDEWALK
	RIGHT-OF-WAY
	OVERHEAD POWER LINE
	ELECTRICAL UNDERGROUND
	GAS LINE
	SANITARY SEWER LINE
	STORM DRAIN LINE
	TELEPHONE LINE
	WATER LINE
	TV CABLE
	CURB INLET
	EMERGENCY VEHICLE PRE-EMPTION DETECTOR
	FIRE HYDRANT
	STREET LIGHT
	PEDESTRIAN SIGNAL HEAD
	PULL BOX/UTILITY VAULT
	SERVICE CABINET
	CONTROLLER CABINET
	TRAFFIC SIGN
	TRAFFIC SIGNAL HEAD
	TRAFFIC SIGNAL MAST ARM SIGN
	VIDEO MONITORING CAMERA
	MS SEDCO MICROWAVE DETECTOR
	TRAFFIC LOOPS
	TREE

ABBREVIATIONS

BIU	BUS INTERFACE UNIT
BOW	BACK OF WALK
CB	INSTALL CONDUIT INTO EXISTING PULL BOX
DH	DETECTOR HANDHOLE
DLC	DETECTOR LEAD-IN CABLE
EVP	EMERGENCY VEHICLE PRE-EMPTION
EX, EXIST	EXISTING
FH	FIRE HYDRANT
FOC	FACE OF CURB
LG	LIP OF GUTTER
MIN	MINIMUM
OC	ON CENTER
OLA	OVERLAP A
PB	PULL BOX
PED	PEDESTRIAN
PEU	PHOTOELECTRIC UNIT
PPB	PEDESTRIAN PUSH BUTTON
R/W	RIGHT OF WAY
RC	EQUIPMENT OR MATERIAL TO BE REMOVED AND BECOME THE PROPERTY OF THE CONTRACTOR
RS	REMOVE AND SALVAGE EQUIPMENT
SNS	STREET NAME SIGN
ST	STREET
TYP	TYPICAL



JANUARY 2017

ISSUES/REVISIONS

NO.	DATE	DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT

DRAWN BY: NAP/BUS/MP	DESIGNED BY: NAP/BUS/MP	CHECKED BY: BES	APPROVED BY:
PROJECT NUMBER: 097026201			SCALE: SEE PLAN

TRAFFIC SIGNAL GENERAL NOTES

GN-01


E

D


C

B


A




DETAIL 'A'
5-SECTION SIGNAL HEAD
NOT TO SCALE




DETAIL 'B'
TRANSIT SIGNAL HEAD
(2-SECTION SIGNAL HEAD)
NOT TO SCALE
(1) LENS WILL BE USED IN FLASHING MODE TO INDICATE "PREPARE TO STOP"




DETAIL 'C'
R3-7(R) SIGN
(BLACK ON WHITE BACKGROUND)
NOT TO SCALE




DETAIL 'D'
"RAPID BUS SIGNAL" SIGN
(BLACK ON WHITE BACKGROUND)
NOT TO SCALE




DETAIL 'E'
"BUS EXEMPT" SIGN
(BLACK ON WHITE BACKGROUND)
NOT TO SCALE




DETAIL 'F'
MODIFIED R3-7(R) SIGN
(BLACK ON WHITE BACKGROUND)
NOT TO SCALE



DETAIL 'G'
NO RIGHT TURN
BLANK-OUT SIGN (R3-1)
NOT TO SCALE



DETAIL 'H'
NO RIGHT TURN
BLANK-OUT SIGN (R3-1)
NOT TO SCALE



DETAIL 'Q'
PCC PAD AROUND SIGNAL
POLE AND PULL BOXES
NOT TO SCALE

NOTES:

1. CONCRETE PAD SHALL BE A MINIMUM OF 4" IN DEPTH BELOW THE GROUND AND CONFORM TO CALTRANS REVISED STANDARD SPECIAL PROVISIONS 87-1.03(3).
2. CONTRACTOR SHALL INSTALL GROUT AT THE BOTTOM OF THE PULL BOX PER REVISED CALTRANS STANDARD PLAN ES-8B.

FILE INFO: K:\BAY_IPTO\097026201 - MTC - Dublin Field Elements - NAP\CAD\Drawings\TS-20 Details.dwg

CA: 1-800-227-2600
CALL BEFORE YOU DIG
UNDERGROUND SERVICE ALERT
CALL TWO WORKING DAYS BEFORE YOU DIG

Kimley»Horn
© 2017 KIMLEY-HORN AND ASSOCIATES, INC.
4637 CHABOT DR., SUITE 300, PLEASANTON, CA 94588
PHONE: 925-398-4840
WWW.KIMLEY-HORN.COM



JANUARY 2017

ISSUES/REVISIONS

NO.	DATE	DESCRIPTION

**DUBLIN BOULEVARD
FIELD ELEMENTS
CONSTRUCTION
PROJECT**

DESIGNED BY: NAP/BUS/MP
CHECKED BY: NAP/BUS/MP
BES
APPROVED BY: [Signature]
PROJECT NUMBER: 097026201
SCALE: SEE PLAN

**TRAFFIC SIGNAL
DETAILS**

DT-01

3 OF 26



JANUARY 2017

ISSUES/REVISIONS


NO. DATE DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT

DRAWN BY: NAP/BUS/MP
DESIGNED BY: NAP/BUS/MP
CHECKED BY: BES
APPROVED BY:
PROJECT NUMBER: 097026201
SCALE: SEE PLAN

TRAFFIC SIGNAL DETAILS

DT-02




DETAIL 'J' LOCATION OF BLANK-OUT SIGN ON POLE SHAFT NOT TO SCALE

DETAIL 'K' LOCATION OF BLANK-OUT SIGN ON POLE SHAFT NOT TO SCALE


DETAIL 'L' LOCATION OF SIGNS AND SIGNAL HEADS ON SIGNAL POLE SHAFT NOT TO SCALE

DETAIL 'R' LOCATION OF SIGNS AND SIGNAL HEADS ON ON POLE SHAFT NOT TO SCALE



DETAIL 'M' LOCATION OF SIGN AND SIGNAL HEAD ON 1-B POLE NOT TO SCALE

DETAIL 'N' LOCATION OF BLANK-OUT SIGN ON TYPE 1-B POLE NOT TO SCALE



DETAIL 'P' LOCATION OF SIGN ON MAST ARM AND SIGNAL HEADS ON SIGNAL POLE SHAFT NOT TO SCALE

FILE INFO: K:\BAY_TPTO\097026201 - MTC - Dublin Field Elements - NAP\CAO\Plansheets\TS-21 Details_2.dwg



CONSTRUCTION NOTES (THIS SHEET ONLY)

- INSTALL OWNER FURNISHED INTERSECTOR BICYCLE/VEHICLE MICROWAVE DETECTOR ON SIGNAL MAST ARM PER SPECIFICATIONS. CONTRACTOR TO COORDINATE WITH THE ENGINEER AND WESTERN PACIFIC SIGNAL REPRESENTATIVE FOR PROGRAMMING MICROWAVE DETECTION ZONES.
- FURNISH AND INSTALL DETECTOR CARD RACK. INSTALL OWNER FURNISHED TC1PI-4 INTERSECTOR POWER INJECTOR AND FOUR (4) TC1B INTERFACE BOARDS FOR INTERSECTOR DETECTORS IN EXISTING CABINET. FURNISH AND INSTALL ETHERNET PATCH CABLES BETWEEN THE POWER INJECTOR AND INTERFACE BOARDS.
- FURNISH AND INSTALL PPB COMMON TO EACH PEDESTRIAN PHASE AS SHOWN BY THE CONDUCTOR SCHEDULE. COIL AT LEAST 20 FEET OF WIRE IN PULL BOX NEXT TO SIGNAL POLE WITH PUSH BUTTON. LABEL EACH WIRE WITH PHASE NUMBER.
- DISCONNECT TWO EXISTING BACK LOOPS AT CLOSEST PULL BOX. ABANDON LOOP WIRE IN PLACE.
- DISCONNECT EXISTING COUNT LOOPS AT THE CONTROLLER CABINET AND ABANDON IN PLACE.
- FURNISH AND INSTALL ONE ETHERNET EXTENDER INSIDE THE SIGNAL POLE HANDHOLE, TO EXTEND ETHERNET CABLE TO INTERSECTOR DETECTOR LOCATED ON POLE (E).


SEE DRAWING GN-01 FOR TRAFFIC SIGNAL GENERAL NOTES

AWG OR CABLE	CONDUCTOR SCHEDULE	NUMBER OF CONDUCTORS																		
		RUN NUMBER																		
		1	2	3	4	5	6	7	8	9	10	11	12	13	14					
NO. 14	Ø4 PPB COMMON	(2)	(2)	(1)	(1)						(1)	(1)	(1)	(1)						
	Ø6 PPB COMMON	(2)	(2)	(1)	(1)															
	Ø8 PPB COMMON	(2)	(1)										(1)	(1)						
TOTAL NO. 14		87	67	53	47	33	29	24	22	11	3	3	11	23	23	28	33	23	33	2
NO. 8	TOTAL NO. 8	3	6	3	3	3	1						3	3	3	3	3	3		
NO. 6	TOTAL NO. 6	2																		
3/8" PULL ROPE	TOTAL PULL ROPE	2								1	1									
SIGNAL INTERCONNECT CABLE (SIC)	TOTAL SIC	1	1	1	1	1	1	1	1											
DETECTOR LEAD-IN CABLE	TOTAL DLC	47	47	24	17	12	12	9						8	13	13	18	24		
EVP CABLES	TOTAL CABLE	4	3	1	1	1								1	1	1	2	2	2	2
MICROWAVE DETECTION CABLE (CAT 5E)	Ø2 & Ø5	(1)	(1)	(1)	(1)	(1)	(1)	(1)												
	Ø4 & Ø7	(1)	(1)	(1)	(1)	(1)														
	Ø3 & Ø8	(1)	(1)																	
	Ø1 & Ø6	(1)	(1)																	
	TOTAL CABLE	(4)	(4)	(2)	(2)	(2)	(1)	(1)	(1)											
CONDUIT FILL (%)		24%	21%	40%	33%	27%	19%	16%	3%	7%	17%	21%	24%	30%	35%					
CONDUIT SIZE (IN)		2-4"	2-4"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"			

CONDUCTOR SCHEDULE NOTES (THIS SHEET ONLY)

ALL CONDUITS, CABLES, AND CONDUCTORS ARE EXISTING UNLESS OTHERWISE NOTED.
 ○ = NEW CABLE OR CONDUCTOR
 △ = EXISTING CONDUIT RUN

DRAWINGS MAY NOT INCLUDE ALL RECENT UPDATES. FIELD VERIFICATION IS RECOMMENDED.



PROJECT NOTES:

- FURNISH AND INSTALL A TYPE 90 CONTROLLER ASSEMBLY IN A TYPE "B" CABINET (SEE FOUNDATION DETAIL ES-18) AND SPECIFIC PROVISIONS).
- FURNISH AND INSTALL TYPE II-B SERVICE EQUIPMENT (120/240V) CONSISTING OF:
 MAIN - 100A, 120V, 2P CKT BKR
 SIGNALS (METERED) - 15A, 120V, 1P CKT BKR
 IRIS (METERED) - 15A, 120V, 1P CKT BKR
 CITY ENTRANCE SIGN (METERED) - 15A, 120V, 1P CKT BKR
 SAFETY LIGHTING (UNMETERED) - 20A, 120V, 1P CKT BKR
 STREET LIGHTING (UNMETERED) - 15A, 120V, 1P CKT BKR
 IRRIGATION (METERED) - 15A, 120V, 1P CKT BKR
 120V CONDUCTOR FOR STREET LIGHTING
 120V CONDUCTOR FOR CITY ENTRANCE SIGN
- FURNISH AND INSTALL "3M-OPTICOM" BRAND EVP DETECTOR (OR EQUAL) ON 3/4" PIPE THREADED INTO TOP OF SIGNAL MAST ARM.

LEGEND:

- = "PHASE LOOP"
- (E) = EXISTING
- * = INDICATES SENSOR UNIT WITH EXTENSION/DELAY CAPABILITY
- * * = INDICATES FIVE (5) SECTION HEAD, SEE TR-1A FOR DETAIL
- △ = SEE SIGN SCHEDULE ON SHEET TR-1A FOR SIGN DESIGNATION

GENERAL NOTES:

- ALL PULL BOXES SHALL BE NO. 5 UNLESS OTHERWISE NOTED ON PLAN.
- POSITIONING OF POLES, PULL BOXES, CONTROLLER CABINET, SERVICE CABINET AND DETECTOR LOOPS SHALL BE VERIFIED BY THE ENGINEER PRIOR TO INSTALLATION.
- LOOP DETECTOR SHALL BE CENTERED IN EFFECTIVE LANE WIDTHS UNLESS OTHERWISE NOTED ON PLAN OR DIRECTED BY THE ENGINEER.
- SERVICE INSTALLATION SHALL MEET THE REQUIREMENTS OF THE CITY'S BUILDING INSPECTOR DEPARTMENT AND P.E. AND PASS ALL INSPECTIONS PRIOR TO ENERGIZING THE SIGNAL OR LIGHTING SYSTEM.
- SIGNAL HEAD BACKPLATES SHALL BE SOLID METAL TYPE.
- TRAFFIC SIGNAL HEADS SHALL BE ALUMINUM.
- SEE STATE STD. PLANS ES-1A AND ES-1B FOR ADDITIONAL LEGEND, SYMBOLS AND ABBREVIATIONS.
- SEE STATE STD. PLAN ES-17 FOR TYPICAL SIGNAL STANDARD PLACEMENT DIMENSIONS AND DETAILS.
- CONDUIT ROUTING SHALL BE ESSENTIALLY DIAGRAMMATIC. CONTRACTOR SHALL LAY OUT RIGID TO SUIT FIELD CONDITIONS AND THE COORDINATION REQUIREMENTS OF UTILITIES OR ANY OTHER TRADES. UPON COMPLETION OF CONDUIT INSTALLATION, THE ACTUAL LOCATION OF CONDUITS SHALL BE NOTED ON A AS-BUILT SET OF PRINTS AND FURNISHED TO THE CITY.
- CONTRACTOR SHALL NOTIFY UNDERGROUND SERVICE ALERT (USA) TWO WORKING DAYS PRIOR TO ANY WORK. CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATING ALL UTILITIES.
- THIS PLAN IS ACCURATE FOR ELECTRICAL WORK ONLY.
- SEE SPECIFICATIONS FOR CONTRACTOR FOR SAN RAMON ROAD STREET LIGHTING.

DUBLIN BOULEVARD WIDENING PROJECT
 TRAFFIC SIGNAL PLAN
 DUBLIN BLVD @ SAN RAMON RD
 DUBLIN, CALIFORNIA

PREPARED BY
SANTINA THOMPSON, INC.
 1455 WILLOW WAY, SUITE 280
 CONCORD, CALIFORNIA 94520
 (510) 827-3200

CITY OF DUBLIN
 City Offices, 100 Civic Plaza, Dublin, California 94568
 Public Works Department - Engineering, (510) 833-4630

DATE:	8/16/95	NO. DATE:	
DESIGN:		REVISIONS:	
DRAWN:	TJM		
CHECKED:	PH		
SCALE:	1" = 20'		
JOB NO. 0220		DRAWING No. 95-01-17	
SHEET 17 OF 26 SHEETS			

Kimley Horn
 © 2017 KIMLEY-HORN AND ASSOCIATES, INC.
 4637 CHABOT DR., SUITE 300, PLEASANTON, CA 94588
 PHONE: 925-398-4840
 WWW.KIMLEY-HORN.COM




JANUARY 2017

ISSUES/REVISIONS

NO.	DATE	DESCRIPTION
-----	------	-------------

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT



DRAWN BY:	DESIGNED BY:	CHECKED BY:	APPROVED BY:
NAP/BUS/MP	NAP/BUS/MP	BES	

PROJECT NUMBER: 097026201
 SCALE: SEE PLAN

TS-01

AS-BUILT DATED 1-17-1995. SEE NOTE 11 UNDER TRAFFIC SIGNAL GENERAL NOTES ON GN-01.

FILE INFO: K:\BAY_IPTO\097026201 - MTC - Dublin Field Elements - NAP\CAD\Plansheets\TS-01 Dublin & San Ramon.dwg BY:mikto,petrov





CONSTRUCTION NOTES (THIS SHEET ONLY)

- 1 REWIRE LOOP DETECTOR LEAD-IN CABLES IN THE CABINET SO THAT EACH DETECTOR IS WIRED TO ITS OWN CHANNEL. PROVIDE DIAGRAM SHOWING HOW CABLES ARE LANDED IN THE CABINET. LABEL EACH WIRE WITH PHASE AND DETECTOR NUMBER.
- 2 DISCONNECT TWO EXISTING BACK LOOPS AT CLOSEST PULL BOX. ABANDON LOOP WIRE IN PLACE.

DRAWINGS MAY NOT INCLUDE ALL RECENT UPDATES. FIELD VERIFICATION IS RECOMMENDED.

SEE DRAWING GN-01 FOR TRAFFIC SIGNAL GENERAL NOTES




APPLICABLE CALTRANS STANDARD PLANS (JULY 1992)

ES-1A	ES-3A	ES-3E	ES-3C	ES-6M	ES-8
ES-1B	ES-3B	ES-4A	ES-5E	ES-6MA	ES-10
ES-2A	ES-3C	ES-5A	ES-6A	ES-6S	ES-13
ES-2B	ES-3D	ES-5B	ES-6AA	ES-6T	ES-33

LEGEND:

○ = "PHASE LOOP"
 (E) = EXISTING
 * = INDICATES SENSOR UNIT WITH EXTENSION OR DELAY CAPABILITY

BEFORE EXCAVATING
 CALL U.S.A.
 UNDERGROUND SERVICE ALERT
 (800) 227-2600
 TOLL FREE
 TWO WORK DAYS BEFORE ALL
 PLANNED WORK OPERATIONS



PROJECT NOTES:

- 1 FURNISH AND INSTALL A TYPE 90 CONTROLLER ASSEMBLY IN A TYPE "A" CABINET (SEE FOUNDATION DETAIL ES-10 AND SPECIAL PROVISIONS).
- 2 FURNISH AND INSTALL TYPE III-AF SERVICE EQUIPMENT (120/240V) CONSISTING OF:
 MAIN - 100A, 120V, 3P 4W, 1P CKT BKR
 SIGNALS (METERED) - 15A, 120V, 1P CKT BKR
 ISNS (METERED) - 15A, 120V, 1P CKT BKR
 SAFETY LIGHTING (UNMETERED) - 20A, 120V, 1P CKT BKR
 STREET LIGHTING (UNMETERED) - 20A, 120V, 1P CKT BKR
 IRRIGATION (UNMETERED) - 15A, 120V, 1P CKT BKR
- 3 FURNISH AND INSTALL "3M-OPTICOM" BRIDGE VEP DETECTOR (OR EQUIVALENT 3/4" PIPE THREADED INTO TOP OF SIGNAL MAST).
- 4 REPLACE EXISTING PULL BOX WITH NEW No.6 PULL BOX.

GENERAL NOTES:

- 1 ALL PULL BOXES SHALL BE No.5 UNLESS OTHERWISE NOTED ON PLAN.
- 2 POSITIONING OF POLES, PULL BOXES, CONTROLLER CABINET, SERVICE CABINET AND DETECTOR LOOPS SHALL BE VERIFIED BY THE ENGINEER PRIOR TO INSTALLATION.
- 3 LOOP DETECTORS SHALL BE CENTERED IN EFFECTIVE LANE WIDTHS UNLESS OTHERWISE NOTED ON PLAN OR DIRECTED BY THE ENGINEER.
- 4 SERVICE INSTALLATIONS SHALL MEET THE REQUIREMENTS OF THE CITY'S BUILDING INSPECTION DEPARTMENT AND P.C.S.E. AND PASS ALL INSPECTIONS PRIOR TO ENERGIZING THE SIGNAL OR LIGHTING SYSTEM.
- 5 SIGNAL HEAD BACKPLATES SHALL BE SOLID METAL TYPE.
- 6 TRAFFIC SIGNAL HEADS SHALL BE METAL (ALUMINUM).
- 7 SEE STATE STD. PLANS ES-1A AND ES-1B FOR LEGEND, SYMBOLS AND ABBREVIATIONS.
- 8 SEE STATE STD. PLAN ES-3C FOR TYPICAL SIGNAL STANDARD PLACEMENT DIMENSIONS AND DETAILS.
- 9 CONDUIT ROUTING SHOWN IS ESSENTIALLY DIAGRAMATIC. CONTRACTOR SHALL LAYOUT RUNS TO SUIT FIELD CONDITIONS AND THE COORDINATION REQUIREMENTS OF UTILITIES OR ANY OTHER TRADES. UPON COMPLETION OF CONDUIT INSTALLATION, THE ACTUAL LOCATION OF CONDUITS SHALL BE NOTED ON AN AS-BUILT SET OF PRINTS AND FURNISHED TO THE CITY.

THIS PLAN IS ACCURATE FOR ELECTRICAL WORK ONLY.

8/15/95
 DUBLIN BOULEVARD
 WIDENING PROJECT
 TRAFFIC SIGNAL PLAN
 DUBLIN BLVD @ REGIONAL ST
 DUBLIN CALIFORNIA

PREPARED BY
SANTINA THOMPSON, INC.
 1355 WILLOW WAY, SUITE 280
 CONCORD, CALIFORNIA 94520
 (510) 827-3200

PREPARED FOR
CITY OF DUBLIN
 City Offices, 100 Civic Plaza, Dublin, California 94568
 Public Works Department - Engineering, (510) 833-6830

DATE: 07/15/95	DESIGNED BY: NAP/BUS/MP	CHECKED BY: BES	APPROVED BY:
DRAWN BY: TJM	PROJECT NUMBER: 097026201	SCALE: SEE PLAN	
JOB No. 0220	DRAWING No. 95-01-19		
SHEET 19 OF 26 SHEETS			




JANUARY 2017

ISSUES/REVISIONS

NO.	DATE	DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT



DRAWN BY: NAP/BUS/MP
 DESIGNED BY: NAP/BUS/MP
 CHECKED BY: BES
 APPROVED BY:
 PROJECT NUMBER: 097026201
 SCALE: SEE PLAN

**TRAFFIC SIGNAL PLAN
 DUBLIN BLVD &
 REGIONAL ST**

TS-02

FILE INFO: K:\BAY_TPTO\097026201 - MTC - Dublin Field Elements - NAP\CAD\Plansheets\TS-02 Dublin & Regional.dwg
 B:\nrikta.petrov
 C:\n
 4




AS-BUILT DATED 1-19-1995. SEE NOTE 11 UNDER TRAFFIC SIGNAL GENERAL NOTES ON GN-01.

CONSTRUCTION NOTES (THIS SHEET ONLY)

- REWIRE LOOP DETECTOR LEAD-IN CABLES IN THE CABINET SO THAT EACH DETECTOR IS WIRED TO ITS OWN CHANNEL. PROVIDE DIAGRAM SHOWING HOW CABLES ARE LANDED IN THE CABINET. LABEL EACH WIRE WITH PHASE AND DETECTOR NUMBER.
- DISCONNECT TWO EXISTING BACK LOOPS AT CLOSEST PULL BOX. ABANDON LOOP WIRE IN PLACE.

SEE DRAWING GN-01 FOR TRAFFIC SIGNAL GENERAL NOTES

DRAWINGS MAY NOT INCLUDE ALL RECENT UPDATES. FIELD VERIFICATION IS RECOMMENDED.




JANUARY 2017

ISSUES/REVISIONS

NO. DATE DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT



DESIGNED BY: NAP/BUS/MP
 CHECKED BY: BES
 PROJECT NUMBER: 097026201
 SCALE: SEE PLAN

TRAFFIC SIGNAL PLAN DUBLIN BLVD & GOLDEN GATE DR

TS-03

FILE INFO: K:\BAY_TPTO\097026201 - MTC - Dublin Field Elements - NAP\CAD\Plansheets\TS-03 Dublin & Golden Gate.dwg BY:nikto.petrov



E

D

C

B

A

CONDUCTOR SCHEDULE

AWG OR CABLE	NUMBER OF CONDUCTORS	RUN NUMBER											
		RUN NUMBER											
		1	2	3	4	5	6	7	8	9	10	11	12
NO. 14	Ø2 PPB COMMON	1	1						1	1	1	1	
	Ø4 PPB COMMON	2	2										
	Ø6 PPB COMMON	1	1	1	1								
	Ø8 PPB COMMON	2	2	1	1	1	1	1	1	1	1	1	1
	TOTAL NO. 14	65	65	65	65	65	65	65	65	65	65	65	65
NO. 8	TOTAL NO. 8	4	4	3	3	1	1	3		2	2	4	
3/8" PULL ROPE	TOTAL PULL ROPE	1	1	1	1	1	1	1					
SIGNAL INTERCONNECT CABLE (SIC)	TOTAL SIC	2	2	1	1	1	1						
DETECTOR LEAD-IN CABLE	TOTAL DLC	31	31	14	7	7	4	4	3	1	5	7	6
EVP CABLES	TOTAL CABLE	4	4	1	1					1	1	1	2
MICROWAVE DETECTION CABLE (CAT 5E)	Ø2 & Ø5	1	1					1	1	1	1	1	
	Ø4 & Ø7	1	1							1	1	1	
	Ø3 & Ø8	1	1	1	1								
	Ø1 & Ø6	1	1										
	TOTAL CABLE		4	4	1	1				1	1	2	2
CONDUIT FILL (%)		33%	33%	31%	25%	33%	31%	32%	24%	19%	15%	16%	17%
CONDUIT SIZE (IN)		2-3"	2-3"	3"	3"	2"	2"	2"	2"	2"	3"	3"	3"

CONDUCTOR SCHEDULE NOTES (THIS SHEET ONLY)

ALL CONDUITS, CABLES, AND CONDUCTORS ARE EXISTING UNLESS OTHERWISE NOTED.

○ = NEW CABLE OR CONDUCTOR

△ = EXISTING CONDUIT RUN

DRAWINGS MAY NOT INCLUDE ALL RECENT UPDATES. FIELD VERIFICATION IS RECOMMENDED.

CONSTRUCTION NOTES (THIS SHEET ONLY)

- INSTALL OWNER FURNISHED INTERSECTOR BICYCLE/VEHICLE MICROWAVE DETECTOR ON SIGNAL MAST ARM PER SPECIFICATIONS. CONTRACTOR TO COORDINATE WITH THE ENGINEER AND WESTERN PACIFIC SIGNAL REPRESENTATIVE FOR PROGRAMMING MICROWAVE DETECTION ZONES.
- FURNISH AND INSTALL DETECTOR CARD RACK. INSTALL OWNER FURNISHED TCPI-4 INTERSECTOR POWER INJECTOR AND FOUR (4) TCIB INTERFACE BOARDS FOR INTERSECTOR DETECTORS IN EXISTING CABINET. FURNISH AND INSTALL ETHERNET PATCH CABLES BETWEEN THE POWER INJECTOR AND INTERFACE BOARDS.
- FURNISH AND INSTALL PPB COMMON TO EACH PEDESTRIAN PHASE AS SHOWN BY THE CONDUCTOR SCHEDULE. COIL AT LEAST 20 FEET OF WIRE IN PULL BOX NEXT TO SIGNAL POLE WITH PUSH BUTTON. LABEL EACH WIRE WITH PHASE NUMBER.
- DISCONNECT TWO EXISTING BACK LOOPS AT CLOSEST PULL BOX. ABANDON LOOP WIRE IN PLACE.
- FURNISH AND INSTALL ONE ETHERNET EXTENDER INSIDE THE SIGNAL POLE HANDHOLE, TO EXTEND ETHERNET CABLE TO INTERSECTOR DETECTOR LOCATED ON POLE (F).

SEE DRAWING GN-01 FOR TRAFFIC SIGNAL GENERAL NOTES

Kimley Horn
 © 2017 KIMLEY-HORN AND ASSOCIATES, INC.
 4637 CHABOT DR., SUITE 300, PLEASANTON, CA 94588
 PHONE: 925-398-4840
 WWW.KIMLEY-HORN.COM




JANUARY 2017

ISSUES/REVISIONS

NO. DATE DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT

NORTH




DESIGNED BY: NAP/BUS/MP
 CHECKED BY: BES
 PROJECT NUMBER: 097026201
 SCALE: SEE PLAN

TRAFFIC SIGNAL PLAN DUBLIN BLVD & AMADOR PLAZA RD

TS-04

8 OF 26



GENERAL NOTES

ALL MATERIAL AND WORKMANSHIP SHALL FULLY CONFORM TO THE NATIONAL ELECTRICAL CODE, THE STATE STANDARD SPECIFICATIONS, THE CITY OF DUBLIN TRAFFIC SIGNAL SPECIFICATIONS AND DETAILS. WHERE THERE IS A CONFLICT, THE MORE RESTRICTIVE SHALL APPLY.

LOCATIONS OF STANDARDS, PULL BOXES, AND OTHER EQUIPMENT SHOWN ON THIS PLAN ARE APPROXIMATE AND SHALL BE LOCATED IN THE FIELD BY THE ENGINEER. THE LOCATION SHALL BE DETERMINED PRIOR TO DRILLING FOR FOUNDATIONS.

DRAWINGS ARE SCHEMATIC IN NATURE. THE CONTRACTOR IS RESPONSIBLE FOR CONSTRUCTING A COMPLETE AND FUNCTIONAL TRAFFIC SIGNAL ACCORDING TO CITY OF DUBLIN SPECIFICATIONS. ANY PERCEIVED ANOMALIES SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER IN A TIMELY MANNER.

THE CONTRACTOR SHALL NOTIFY UNDERGROUND SERVICE ALERT A MINIMUM OF TWENTY-FOUR (24) HOURS PRIOR TO ANY EXCAVATION. THE CONTRACTOR IS RESPONSIBLE FOR COMPLYING WITH ALL REQUIRED CLEARANCES FROM OVERHEAD AND UNDERGROUND UTILITIES.

ALL CONDUIT AND FITTINGS SHALL BE UL APPROVED. THE MINIMUM RADIUS OF BENDS SHALL BE 18 INCHES. ALL BENDS AND/OR OFFSETS SHALL BE ACCOMPLISHED WITH FACTORY FORMED SECTIONS. ALL EMPTY CONDUIT ENDS SHALL BE PLUGGED. ALL OTHER CONDUIT SHALL HAVE BELL ENDS AND SHALL BE SEALED WITH DUCT SEAL. THE UNDERGROUND CONDUIT AND ALL METAL PARTS SHALL BE CONTINUOUSLY BONDED AND GROUND. PROVIDE A #10 PULL WIRE IN ALL EMPTY CONDUITS. ALL CROSSINGS SHALL BE PERPENDICULAR TO THE STREET. SIGNAL INTERCONNECT CONDUIT SHALL COMPLY WITH THE SPECIAL PROVISIONS AND SHALL BE ENTIRELY SEPARATE FROM OTHER CONDUITS.

CONDUIT SHALL BE INSTALLED AT A MINIMUM DEPTH OF 24" BELOW SIDEWALKS OR PLANTER STRIPS AND 36" BELOW ROADWAYS. REFER TO THE SPECIFICATION FOR ADDITIONAL INFORMATION REGARDING SPECIFIC LOCATIONS.

REFER TO THE CITY OF DUBLIN TRAFFIC SIGNAL SPECIFICATION. NO MECHANICAL MEANS SHALL BE USED TO PULL WIRE.


ALL SIGNAL HEADS SHALL 12" AND SHALL HAVE BACKPLATES.

CITY OF DUBLIN PUBLIC WORKS
 REVIEW OF PLANS DOES NOT RELIEVE THE OWNER/DEVELOPER OF RESPONSIBILITY FOR CORRECTION OF MISTAKES, ERRORS OR OMISSIONS. FINAL APPROVAL OF CONSTRUCTION OR INSTALLATION SUBJECT TO INSPECTION, TEST AND ACCEPTANCE.

REVIEWED BY: [Signature]
 DUBLIN PUBLIC WORKS DIRECTOR/CITY ENGINEER
 DATE: 7/9/01


AS-BUILT DATED 6-25-2001. SEE NOTE 11 UNDER TRAFFIC SIGNAL GENERAL NOTES ON GN-01.

FILE INFO: K:\BAY_TPTO\097026201 - MTC - Dublin Field Elements - NAP\CAD\Plansheets\TS-04 Dublin & Amador Plaza.dwg
 BY: mtkto,petroy
 CA: 1-800-227-2600
 CALL BEFORE YOU DIG
 UNDERGROUND SERVICE ALERT
 CALL TWO WORKING DAYS BEFORE YOU DIG



EXISTING PHASE DIAGRAM

EMERGENCY VEHICLE PREEMPTION
 eva = 02 & 05
 evb = 04 & 07
 evc = 01 & 06
 evd = 03 & 08



PROPOSED PHASE DIAGRAM

EMERGENCY VEHICLE PREEMPTION
 eva = 02 & 05
 evb = 04 & 07
 evc = 01 & 06
 evd = 03 & 08
 09 ACTIVATED BY TSP

*BLANK-OUT SIGN TO BE ACTIVE DURING THIS PHASE




PROPOSED RING-BARRIER DIAGRAM

RING 1	01	02	BARRIER	03	04	BARRIER
RING 2	05	09	06	07	08	

CONSTRUCTION NOTES (THIS SHEET ONLY)

1. INSTALL OWNER-FURNISHED INTERSECTOR BICYCLE/VEHICLE MICROWAVE DETECTOR ON SIGNAL MAST ARM PER MANUFACTURER'S SPECIFICATIONS. CONTRACTOR TO COORDINATE WITH THE ENGINEER AND WESTERN PACIFIC SIGNAL REPRESENTATIVE FOR MICROWAVE DETECTION ZONES.
2. FURNISH AND INSTALL DETECTOR CARD RACK. INSTALL OWNER FURNISHED TOPI-4 INTERSECTOR POWER INJECTOR AND FOUR (4) TCIB INTERFACE BOARDS FOR INTERSECTOR DETECTORS IN EXISTING CABINET. FURNISH AND INSTALL ETHERNET PATCH CABLES BETWEEN THE POWER INJECTOR AND INTERFACE BOARDS.
3. FURNISH AND INSTALL PPB COMMON TO EACH PEDESTRIAN PHASE AS SHOWN BY THE CONDUCTOR SCHEDULE. COIL AT LEAST 20 FEET OF WIRE IN PULL BOX NEXT TO SIGNAL POLE WITH PUSH BUTTON. LABEL EACH WIRE WITH PHASE NUMBER.
4. DISCONNECT TWO EXISTING BACK LOOPS AT CLOSEST PULL BOX. ABANDON LOOP WIRE IN PLACE.
5. REWIRE LOOP DETECTOR LEAD-IN CABLES IN THE CABINET SO THAT EACH DETECTOR IS WIRED TO ITS OWN CHANNEL. PROVIDE DIAGRAM SHOWING HOW CABLES ARE LANDED IN THE CABINET. LABEL EACH WIRE WITH PHASE AND DETECTOR NUMBER.
6. FURNISH AND INSTALL TRANSIT SIGNAL HEAD, "BUS SIGNAL" SIGN, AND 5-SECTION TRAFFIC SIGNAL HEAD PER DETAIL 'P' ON DRAWING DT-02.
7. FURNISH AND INSTALL 5-SECTION TRAFFIC SIGNAL HEAD AND MODIFIED R3-7 SIGN PER DETAIL 'M' ON DRAWING DT-02.
8. FURNISH AND INSTALL LED R3-1 "NO RIGHT TURN" BLANK-OUT SIGN ON EXISTING POLE PER DETAIL 'K' ON DRAWING DT-02. WIRE THE SIGN WITH BUS PHASE. SIGN TO BE ACTIVE DURING THAT PHASE ONLY.
9. FURNISH AND INSTALL LED R3-1 "NO RIGHT TURN" BLANK-OUT SIGN PER DETAIL 'J' ON DRAWING DT-02. WIRE THE SIGN WITH BUS PHASE. SIGN TO BE ACTIVE DURING THAT PHASE ONLY.
10. FURNISH AND INSTALL ONE ETHERNET EXTENDER INSIDE THE SIGNAL POLE HANDHOLE, TO EXTEND ETHERNET CABLE TO INTERSECTOR DETECTOR LOCATED ON POLE (A).
11. FURNISH AND INSTALL ONE ETHERNET EXTENDER INSIDE THE SIGNAL POLE HANDHOLE, TO EXTEND ETHERNET CABLE TO INTERSECTOR DETECTOR LOCATED ON POLE (G).

SEE DRAWING GN-01 FOR TRAFFIC SIGNAL GENERAL NOTES




JANUARY 2017

ISSUES/REVISIONS

NO. DATE DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT



DRAWN BY: NAP/BUS/MP
 DESIGNED BY: NAP/BUS/MP
 CHECKED BY: BES
 APPROVED BY:
 PROJECT NUMBER: 097026201
 SCALE: SEE PLAN

TRAFFIC SIGNAL PLAN DUBLIN BLVD & VILLAGE PKWY

TS-05

FILE INFO: K:\BAY_IPTO\097026201 - MTC - Dublin Field Elements - NAP\CAD\Plansheets\TS-06 Dublin & Village_Schedule.dwg BY:nkita.petrov

CONDUCTOR SCHEDULE													
AWG OR CABLE	NUMBER OF CONDUCTORS												
	RUN NUMBER												
	1	2	3	4	5	6	7	8	9	10	11	12	
NO. 14	Ø1	6	6	3	3	3	3		3	3	3	3	
	Ø2	6	6	3	3	3	3		3	3	3	3	
	Ø3	3	3							3	3	3	
	Ø4	6	6	3	3	3				3	3	3	
	Ø5	3	3	3									
	Ø6	3	3						3	3	3	3	
	Ø7	3	3	3	3	3							
	Ø8	3	3									3	
	Ø9	4	4						4	4	4	4	
	Ø2P	2	2	2	2	2							
	Ø4P	4	4	2	2	2				2	2	2	
	Ø6P	2	2						2	2	2	2	
	Ø8P	4	4	2	2							2	
	Ø2PPB	2	2	2	2	2							
	Ø4PPB	4	4	2	2	2			2	2	2	2	
	Ø6PPB	2	2						2	2	2	2	
	Ø8PPB	4	4	2	2							2	
	Ø2 PPB COMMON	①	①	①	①	①							
	Ø4 PPB COMMON	②	②	①	①	①			①	①	①	①	
	Ø6 PPB COMMON	①	①						①	①	①	①	
	Ø8 PPB COMMON	②	②	①	①							①	
	IISNS		4	2	2	2				2	2	2	
	BLANK-OUT SIGN	④	④	②	②	②				②	②	②	
	SPARES	6	6	3	3	3	3	3	3	3	3	3	
	TOTAL NO. 14	19/63	19/67	5/32	5/29	4/25	9	①/6	6/20	8/28	8/28	9/35	
	NO. 8	LIGHTING		4	2	2	2				2	2	2
		SIGNAL NEUTRAL	2	2	1	1	1	1	1	1	1	1	1
		TOTAL NO. 8	2	6	3	3	3	3	1	1	3	3	3
NO. 6	120V CONTROLLER SERVICE	2											
DETECTOR LEAD-IN CABLE	Ø1	1	1	1									
	Ø2	3	3	2	2	2	2	1	1	1	1	1	
	Ø3	1	1	1	1								
	Ø4	3	3							1	3	3	
	Ø5	2	2					2	2	2	2	2	
	Ø6	5	5										
	Ø7	2	2								2	2	
	Ø8	1	1	1	1								
	Ø2 SAMPLER LOOPS	2	2	2									
	Ø6 SAMPLER LOOPS	3	3					3	3	3	3	3	
Ø8 SAMPLER LOOPS	2	2								2	2		
TOTAL DLC	25	25	7	4	2	2	6	6	7	13	13		
EMERGENCY VEHICLE PREEMPTION	EVA	1	1						1	1	1	1	
	EVB	1	1	1	1	1							
	EVC	1	1						1	1	1	1	
	EVD	1	1									1	
	TOTAL EVP CABLE	4	4	1	1	1			2	2	2	3	
MICROWAVE DETECTION CABLE (CAT 5E)	Ø2 & Ø5	①	①	①	①								
	Ø4 & Ø7	①	①	①	①	①							
	Ø3 & Ø8	①	①									①	
	Ø1 & Ø6	①	①						①	①	①	①	
	TOTAL CAT 5E CABLE	④	④	②	②	①			①	①	①	②	
MISC	3/8" PULL ROPE	2	2	1				1	1	1	1	1	
CONDUIT FILL (%)		28%	29%	23%	18%	14%	7%	9%	17%	23%	27%	31%	
CONDUIT SIZE (IN)		2-3"	2-3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	

ALL CONDUITS, CABLES, AND CONDUCTORS ARE EXISTING UNLESS OTHERWISE NOTED.

- = NEW CABLE OR CONDUCTOR
- △ = EXISTING CONDUIT RUN
- * = CONDUIT SIZE TO BE VERIFIED AT NEXT SUBMITTAL




EQUIPMENT SCHEDULE													
LOCATION	STANDARD			LED LUMINAIRE	VEHICLE SIGNAL MOUNTING		PEDESTRIAN SIGNAL		PUSH BUTTON			IISNS LEGEND	SPECIAL NOTES
	TYPE	SIGNAL MAST ARM	LUMINAIRE MAST ARM		MAST ARM	POLE	MOUNT	POLE QUAD	Ø	ARROW	POLE QUAD		
(A)	28-5-80	55'	-	-	2 MAS	SV-3-T ^N	SP-1-T	W N S E	4	←	W N S E	Village Pkwy	INSTALL INTERSECTOR DETECTOR
(B)	15TS	-	15'	133	-	SV-2-T	SP-1-T	W N S E	-	-	-	-	FURNISH AND INSTALL BLANK OUT SIGN
(C)	28-5-80	50'	-	-	2 MAS	SV-1-T	SP-1-T	W N S E	6	←	W N S E	Dublin Blvd	INSTALL INTERSECTOR DETECTOR
(D)	1-B	-	-	-	-	TV-2-T ^N	SP-1-T	W N S E	-	-	-	-	
(E)	EXISTING PG&E POLE	-	15' 15'	-	-	SV-1 SV-1	-	-	-	-	-	-	
(F)	18-1-70	30'	-	-	1 MAS	SV-2-T	SP-2-T	W N S E	2	←	W N S E	Village Pkwy	INSTALL INTERSECTOR DETECTOR
(G)	24-4-80	35'	15'	133	2 MAS	SV-1-T	SP-2-T	W N S E	2	←	W N S E	Dublin Blvd	FURNISH AND INSTALL BLANK OUT SIGN INSTALL INTERSECTOR DETECTOR
(H)	15TS	-	15'	133	-	SV-2-T	-	-	-	-	-	-	
(J)	PEDESTRIAN PUSH BUTTON POST	-	-	-	-	-	-	-	-	-	-	-	

ALL POLES AND EQUIPMENT ARE EXISTING UNLESS OTHERWISE NOTED.

N - NEW EQUIPMENT

OTHER REQUIREMENTS ARE COVERED BY NOTES, LEGEND, SPECIAL PROVISIONS AND CALTRANS STANDARD SPECIFICATIONS. FOR TYPE OF STANDARD, VEHICLE AND PEDESTRIAN MOUNTING, SEE CALTRANS STANDARD PLANS.

FOR THE PURPOSE OF LOCATING NEW AND EXISTING EQUIPMENT ON POLES, DUBLIN BOULEVARD SHALL BE CONSIDERED AN EAST-WEST ROADWAY.



EXISTING SIGNAL EQUIPMENT
SCALE 1"=40'



JANUARY 2017

ISSUES/REVISIONS

NO. DATE DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT

DRAWN BY: NAP/BUS/MP DESIGNED BY: NAP/BUS/MP CHECKED BY: BES APPROVED BY:
PROJECT NUMBER: 097026201 SCALE: SEE PLAN

TRAFFIC SIGNAL SCHEDULES DUBLIN BLVD & VILLAGE PKWY

TS-06

CONSTRUCTION NOTES (THIS SHEET ONLY)

1 DISCONNECT TWO EXISTING BACK LOOPS AT CLOSEST PULL BOX. ABANDON LOOP WIRE IN PLACE.

SEE DRAWING GN-01 FOR TRAFFIC SIGNAL GENERAL NOTES

DRAWINGS MAY NOT INCLUDE ALL RECENT UPDATES. FIELD VERIFICATION IS RECOMMENDED.




JANUARY 2017

ISSUES/REVISIONS

NO.	DATE	DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT




DRAWN BY:	DESIGNED BY:	CHECKED BY:	APPROVED BY:
NAP/BUS/MP	NAP/BUS/MP	BES	

PROJECT NUMBER: 097026201
SCALE: SEE PLAN

TRAFFIC SIGNAL PLAN
DUBLIN BLVD & CLARK AVE

TS-07

11 OF 26



AS-BUILT DATED 3-4-2002. SEE NOTE 11 UNDER TRAFFIC SIGNAL GENERAL NOTES ON GN-01.

FILE INFO: K:\BAY_IPTO\097026201 - MTC - Dublin Field Elements - NAP\CAD\Plansheets\TS-07 Dublin & Clark.dwg BY:nikito.petrov



CONTRACTOR:		INSPECTOR:		DATE COMPLETED:			FEHR & PEERS ASSOCIATES, INC. Transportation Consultants
DESIGNED BY:		DRAWN BY:		CHECKED BY:			NH MM
PLANS PREPARED UNDER SUPERVISION OF							REGISTERED CIVIL ENGINEER DATE 10/9/01 RCE NO. C58564
No.	DATE (APVD)	REVISION					



CITY OF DUBLIN
City Offices, 100 Civic Plaza, Dublin, California 94588
Public Works Department - Engineering, (916) 833-6630

REVIEW BY:

for *Julie D. Pano*
PUBLIC WORKS DIRECTOR/CITY ENGINEER

DATE: 3/4/02

CITY OF DUBLIN
PUBLIC WORKS DEPARTMENT

DUBLIN BOULEVARD AT
CLARK AVENUE
TRAFFIC SIGNAL

DRAWING No.
E-1

SHEET
510 of 103 SHEETS


JOB No. 1001-1528
FILE No. 152801

CONSTRUCTION NOTES (THIS SHEET ONLY)



- 1 DISCONNECT TWO EXISTING BACK LOOPS AT CLOSEST PULL BOX. ABANDON LOOP WIRE IN PLACE.

DRAWINGS MAY NOT INCLUDE ALL RECENT UPDATES. FIELD VERIFICATION IS RECOMMENDED.

SEE DRAWING GN-01 FOR TRAFFIC SIGNAL GENERAL NOTES



- PROJECT NOTES:** (FOR SHEETS E-3 AND E-4 ONLY)
- FURNISH AND INSTALL MODEL 2070 "LITE" CONTROLLER ASSEMBLY IN A TYPE RS-2 TYPE 1 CABINET EQUIPPED ACCORDING TO THE SPECIAL PROVISIONS. FRONT DOOR OF CABINET SHALL FACE EAST.
 - FURNISH AND INSTALL TYPE III-CF SERVICE EQUIPMENT ENCLOSURE PER DETAILS ON STATE STANDARD PLAN ES-2C FOR ES-2F. ENCLOSURE SHALL INCLUDE ITEMS (1) THROUGH (7), (15) THROUGH (17) THROUGH (23) AND THE FOLLOWING ADDITIONAL CIRCUIT BREAKERS: STREET LIGHTING CIRCUIT 3 (NUMBERED)-30A, 240V, 2P; STREET LIGHTING CIRCUIT 4 (NUMBERED)-30A, 240V, 2P; STREET LIGHTING CIRCUIT 5 (NUMBERED)-30A, 240V, 2P.
 - FURNISH AND INSTALL EMERGENCY VEHICLE PREEMPTION DETECTOR UNIT ON .25 mm PIPE NIPPLE THREADED VERTICALLY INTO TOP OF SIGNAL MAST ARM. INSTALL OPTIC DETECTOR CABLE TO CONTROLLER CABINET.
 - IRRIGATION CONTROLLER INSTALLED BY OTHERS. SHOW FOR REFERENCE ONLY. SEE IRRIGATION PLANS PREPARED BY HAYGOOD & ASSOCIATES.
 - COIL LEAD OF EACH IRRIGATION SYSTEM CONDUCTOR IN PULL BOX FOR CONNECTION BY OTHERS.



CONTRACTOR:			INSPECTOR:			DATE COMPLETED:		
FEHR & PEERS ASSOCIATES, INC.			DESIGNED BY: NH			DRAWN BY: NH		
REGISTERED CIVIL ENGINEER			CHECKED BY: MM			PLANS PREPARED UNDER SUPERVISION OF: [Signature]		
DATE 10/9/01			RCE NO. C58564			CITY OF DUBLIN		

FOR GENERAL NOTES AND LEGEND, SEE SHEET E-1
THIS SHEET ACCURATE FOR ELECTRICAL WORK ONLY

REVIEW BY: *Judith D. [Signature]*
PUBLIC WORKS DIRECTOR/CITY ENGINEER
DATE: 3/4/02

CITY OF DUBLIN
PUBLIC WORKS DEPARTMENT
DUBLIN BOULEVARD AT
SIERRA COURT
TRAFFIC SIGNAL

AS-BUILT DATED 3-4-2002. SEE NOTE 11 UNDER TRAFFIC SIGNAL GENERAL NOTES ON GN-01.




JANUARY 2017

ISSUES/REVISIONS

NO.	DATE	DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT



DRAWN BY: NAP/BUS/MP
DESIGNED BY: NAP/BUS/MP
CHECKED BY: BES
APPROVED BY: [Signature]

PROJECT NUMBER: 097026201
SCALE: SEE PLAN

TRAFFIC SIGNAL PLAN
DUBLIN BLVD &
SIERRA CT - CIVIC
PLAZA

TS-08

FILE INFO: K:\BAY_IPTO\097026201 - MTC - Dublin Field Elements - NAP\CAD\Plansheets\TS-08 Dublin & Sierra Ct.dwg BY:mikito.petrov




CONSTRUCTION NOTES (THIS SHEET ONLY)

- 1 DISCONNECT EXISTING BACK LOOP AT CLOSEST PULL BOX. ABANDON LOOP WIRE IN PLACE.
- 2 DISCONNECT TWO EXISTING BACK LOOPS AT CLOSEST PULL BOX. ABANDON LOOP WIRE IN PLACE.

DRAWINGS MAY NOT INCLUDE ALL RECENT UPDATES. FIELD VERIFICATION IS RECOMMENDED.

SEE DRAWING GN-01 FOR TRAFFIC SIGNAL GENERAL NOTES



EXISTING EQUIPMENT TO BE REMOVED AND SALVAGED.

1 PFB POST


DELIVER SALVAGED EQUIPMENT TO ALAMEDA COUNTY MAINTENANCE YARD. CALL (910) 670-5537 FOR APPOINTMENT AND DELIVERY INSTRUCTIONS.

APPLICABLE CALTRANS STANDARD PLANS(MAY 2006)

ES-1A	ES-3A	ES-4C	ES-5B	ES-7B	ES-8
ES-1B	ES-3B	ES-4D	ES-5C	ES-7C	ES-9-10
ES-2A	ES-4A	ES-4E	ES-5D	ES-7D	ES-13A
ES-2B	ES-4B	ES-5A	ES-5E	ES-7E	


PROJECT NOTE:

- 1 EXISTING CONTROLLER AND TYPE I SERVICE EQUIPMENT TO REMAIN.
- 2 EXISTING TYPE II SERVICE EQUIPMENT TO REMAIN.



EXISTING TRAFFIC SIGNAL PHASE DIAGRAM TO REMAIN

EVA=#2, #5
EVC=#6, #7



CONTRACT NO. 097026201
DATE REVISION
AS BUILT
RECORD DRAWING


RECORD DRAWINGS
These plans represent the original design and the changes that have been brought to the attention of the City.



CONTRACT NO.	097026201
DATE COMPLETED	9-30-08
SCALE	1"=20'



DESIGNED BY	EXT	DRAWN BY	RO	CHECKED BY	NVB/JW
PLANS PREPARED UNDER SUPERVISION OF:					
N.V. BERNARDI					
REGISTERED CIVIL ENGINEER					
DATE	9-30-08	RCE NO	45407		



REVIEWED BY:	
PUBLIC WORKS DIRECTOR	
DATE	

DUBLIN BLVD / DOUGHERTY RD INTERSECTION IMPROVEMENT PROJECT

DUBLIN BLVD AND DUBLIN CT TRAFFIC SIGNAL MODIFICATION

DRAWING No	E-4
SHEET	85 of 92
CONTRACT NO	07-01

AS-BUILT DATED 2-17-2009. SEE NOTE 11 UNDER TRAFFIC SIGNAL GENERAL NOTES ON GN-01.




JANUARY 2017

ISSUES/REVISIONS

NO.	DATE	DESCRIPTION
-----	------	-------------

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT



DRAWN BY:	DESIGNED BY:	CHECKED BY:	APPROVED BY:
NAP/BUS/MP	NAP/BUS/MP	BES	
PROJECT NUMBER: 097026201		SCALE: SEE PLAN	

TRAFFIC SIGNAL PLAN DUBLIN BLVD & DUBLIN CT

TS-09

FILE INFO: K:\BAY_TPTO\097026201 - MTC - Dublin Field Elements - NAP\CAO\Plansheets\TS-09 Dublin & Dublin Ct.dwg BY: rnikito.petrov



CONSTRUCTION NOTES (THIS SHEET ONLY)

- 1 INSTALL OWNER FURNISHED INTERSECTOR BICYCLE/VEHICLE MICROWAVE DETECTOR ON SIGNAL MAST ARM PER SPECIFICATIONS. CONTRACTOR TO COORDINATE WITH THE ENGINEER AND WESTERN PACIFIC SIGNAL REPRESENTATIVE FOR PROGRAMMING MICROWAVE DETECTION ZONES.
- 2 INSTALL OWNER-FURNISHED TOPI-4 INTERSECTOR POWER INJECTOR AND FOUR (4) TOBI INTERFACE BOARDS FOR INTERSECTOR DETECTORS IN EXISTING CABINET. FURNISH AND INSTALL ETHERNET PATCH CABLES BETWEEN THE POWER INJECTOR AND INTERFACE BOARDS.
- 3 FURNISH AND INSTALL PPB COMMON TO EACH PEDESTRIAN PHASE AS SHOWN BY THE CONDUCTOR SCHEDULE. COIL AT LEAST 20 FEET OF WIRE IN PULL BOX NEXT TO SIGNAL POLE WITH PUSH BUTTON. LABEL EACH WIRE WITH PHASE NUMBER.
- 4 DISCONNECT TWO EXISTING BACK LOOPS AT CLOSEST PULL BOX. ABANDON LOOP WIRE IN PLACE.
- 5 FURNISH AND INSTALL ONE ETHERNET EXTENDER INSIDE THE SIGNAL POLE HANDHOLE, TO EXTEND ETHERNET CABLE TO INTERSECTOR DETECTOR LOCATED ON POLE F.
- 6 FURNISH AND INSTALL ONE ETHERNET EXTENDER INSIDE THE SIGNAL POLE HANDHOLE, TO EXTEND ETHERNET CABLE TO INTERSECTOR DETECTOR LOCATED ON POLE D.
- 7 ROTATE EXISTING BUS SIGNAL LENSES AND REWIRE TO COMPLY WITH TRANSIT SIGNAL CONFIGURATION AS SHOWN IN DETAIL B ON DRAWING DT-01 AND PER CA MUTCD FIGURE 8C-3(CA).
- 8 REMOVE EXISTING R13A (CA) SIGN AND FURNISH AND INSTALL LED R3-1 "NO RIGHT TURN" BLANK-OUT SIGN ON EXISTING POLE PER DETAIL 'K' ON DRAWING DT-02. WIRE THE SIGN WITH BUS PHASE. SIGN TO BE ACTIVE DURING THAT PHASE ONLY.
- 9 REMOVE EXISTING R13A (CA) SIGN AND FURNISH AND INSTALL LED R3-1 "NO RIGHT TURN" BLANK-OUT SIGN PER DETAIL 'J' ON DRAWING DT-02. WIRE THE SIGN WITH BUS PHASE. SIGN TO BE ACTIVE DURING THAT PHASE ONLY.


SEE DRAWING GN-01 FOR TRAFFIC SIGNAL GENERAL NOTES

AWG OR CABLE		NUMBER OF CONDUCTORS																			
		RUN NUMBER																			
		1	2	3	4	5	6	7	8	9	10	11	12	13							
NO. 14	Ø4 PPB COMMON	2	2	2	2	2	2	2	2	2	2	2	2								
	Ø6 PPB COMMON	2	2	1	1	1															
	Ø8 PPB COMMON	2									1	1	1								
	BLANK OUT SIGN	4	2	2	2	2					2	2	2								
	TOTAL NO. 14	64	10	35	6	29	3	22	3	13	2	13	3	29	6	32	4	5	1	5	10
NO. 12	TOTAL NO. 12	3	3																		
NO. 10	TOTAL NO. 10	2	2	2	2	2	2	2	2	2	2	2									
NO. 8	TOTAL NO. 8	1	3	3	3	3	3	3	3	3	3	3									
SIGNAL INTERCONNECT CABLE (SIC)	TOTAL SIC	1																			
DETECTOR LEAD-IN CABLE	TOTAL DLC	40	12	12	12	10	3	7	7	4	18	18	6	3							
EVP CABLES	TOTAL CABLE	4	2	2	1	1	1	1	1	1	1	2									
CCTV CABLE	TOTAL CABLE	1								1	1	1									
MICROWAVE DETECTION CABLE (CAT 5E)	Ø2 & Ø5	1																			
	Ø4 & Ø7	1																			
	Ø3 & Ø8	1	1	1																	
	Ø1 & Ø6	1	1	1	1	1	1	1	1	1	1	1	2								
	TOTAL CABLE	6	2	2	1	1	1	1	1	1	1	2									
	CONDUIT FILL (%)	18%	14%	25%	21%	19%	11%	13%	18%	3%	21%	23%	9%	4%							
	CONDUIT SIZE (IN)	2-4"	2-3"	3"	3"	3"	3"	3"	3"	3"	3 1/2"	3 1/2"	3"	3"							

CONDUCTOR SCHEDULE NOTES (THIS SHEET ONLY)

ALL CONDUITS, CABLES, AND CONDUCTORS ARE EXISTING UNLESS OTHERWISE NOTED.
 ○ = NEW CABLE OR CONDUCTOR
 △ = EXISTING CONDUIT RUN

DRAWINGS MAY NOT INCLUDE ALL RECENT UPDATES. FIELD VERIFICATION IS RECOMMENDED.



PROJECT NOTES:

- 1 FURNISH AND INSTALL NEW NAZTEC MODEL 980 TYPE 2 TS2 CONTROLLER IN A TYPE P "STRETCH" (TS-2 TYPE 1) CABINET.
- 2 FURNISH AND INSTALL NEW TYPE II-A SERVICE EQUIPMENT ENCLOSURE.
- 3 RELOCATE EXISTING BATTERY BACK-UP SYSTEM FROM EXISTING CONTROLLER CABINET TO NEW CONTROLLER CABINET AT LOCATION (SEE SIC PLAN FOR CONTINUATION).
- 4 FURNISH AND INSTALL INTERNALLY ILLUMINATED STREET NAME SIGN (S/N) ON SIGNAL MAST ARM.
- 5 FURNISH AND INSTALL EVP OPTICOM DETECTOR ON MAST ARM.
- 6 FURNISH AND INSTALL R73-5 SIGN ON MAST ARM.
- 7 FURNISH AND INSTALL MODIFIED R73-6 SIGN ON MAST ARM. SEE DETAIL C ON SHEET E-3.
- 8 FURNISH AND INSTALL 12" 5-SECTION SIGNAL HEAD (SEE DETAIL B).
- 9 RELOCATE EXISTING VIDEO CAMERA AND MOUNTING BRACKET FROM EXISTING MAST ARM. RELOCATE EXISTING CAMERA BOX AND CONTENTS FROM EXISTING SIGNAL MAST ARM.
- 10 INSTALL RELOCATED VIDEO CAMERA ON NEW MAST ARM. INSTALL RELOCATED CAMERA BOX AND CONTENTS ON NEW MAST ARM.
- 11 INSTALL NEW TYPE 1 PEDESTRIAN BARRICADE WITH R49(L1)/(R1).
- 12 INSTALL SPECIAL SIGN ON SIGNAL POLE PER DETAIL C.
- 13 INSTALL CONCRETE PAD (8'x8') FOR TYPE P CABINET.
- 14 INSTALL CITY OF DUBLIN STANDARD 3" FIBER OPTICS CONDUITS AND PULL BOXES. REFER TO 6(E) PULL BOX AND CONDUIT INSTALLATION DETAILS IN PROJECT SPECIFICATIONS.
- 15 FROM THE UPSTREAM PULL BOX CAREFULLY REMOVE THE EXISTING SIGNAL INTERCONNECT CABLES FROM CONDUITS LEADING TO THE EXISTING CONTROLLER AT THE INTERSECTION OF DOUGHERTY ROAD AND SIERRA LANE. DO NOT CUT, SEVER, OR DAMAGE THE EXISTING CABLES. UPON COMPLETION OF INSTALLATION OF CONDUIT, PULL BOX AND NEW CONTROLLER AT THE INTERSECTION OF DOUGHERTY ROAD AND DUBLIN BLVD, REINSTALL THE EXISTING CABLES AS INDICATED IN CONDUIT TO THE NEW CONTROLLER. CONTRACTOR SHALL INSTALL NEW SIGNAL INTERCONNECT CABLES IF THE EXISTING CABLES ARE DAMAGED DURING THE CONSTRUCTION.

EQUIPMENT TO BE REMOVED AND SALVAGE:

1. TYPE 29-5-70 SIGNAL POLE WITH 55' MAST ARM.
2. TYPE 29-5-70 SIGNAL POLE WITH 55' MAST ARM.
3. 24 VEHICLE SIGNAL HEADS
4. 6 PEDESTRIAN SIGNAL HEADS
5. 4 EVP OPTICOM DETECTORS
6. 4 SIGNS
7. 2 TYPE 1 PEDESTRIAN BARRICADES

DELIVER SALVAGED EQUIPMENT ITEM 1 THROUGH 5 TO ALAMEDA COUNTY MAINTENANCE YARD. CALL (510) 422-5537 FOR APPOINTMENT AND DELIVERY INSTRUCTIONS.

DELIVER SALVAGED EQUIPMENT ITEM 6 AND 7 TO CITY OF DUBLIN MAINTENANCE YARD.

APPLICABLE CALTRANS STANDARD PLANS (MAY 2006)

ES-1A	ES-3A	ES-4C	ES-5B	ES-7B	ES-8
ES-1B	ES-3B	ES-4D	ES-5C	ES-7C	ES-10
ES-2A	ES-4A	ES-4E	ES-5E	ES-7H	ES-13A
ES-2B	ES-4B	ES-5A	ES-5D	ES-7D	

FILE INFO: K:\BAY_TPTO\097026201 - MTC - Dublin Field Elements - NAP\CAD\Plansheets\TS-10 Dublin & Dougherty.dwg B:\mknko\petrov
 CA: 1-800-227-2600
 CALL BEFORE YOU DIG
 UNDERGROUND SERVICE ALERT
 CA: 1-800-227-2600
 CALL TWO WORKING DAYS BEFORE YOU DIG



AS-BUILT DATED 2-17-2009. SEE NOTE 11 UNDER TRAFFIC SIGNAL GENERAL NOTES ON GN-01.




JANUARY 2017

ISSUES/REVISIONS

NO.	DATE	DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT



DESIGNED BY: NAP/BUS/MP
 CHECKED BY: BES
 PROJECT NUMBER: 097026201
 SCALE: SEE PLAN

TRAFFIC SIGNAL PLAN DUBLIN BLVD & DOUGHERTY RD

TS-10

14 OF 26


 CITY OF DUBLIN PUBLIC WORKS DEPARTMENT City Office, 100 Civic Plaza, Dublin, California 94568	DESIGNED BY: EKT DRAWN BY: RD CHECKED BY: NVB/JW PLANS PREPARED UNDER SUPERVISION OF: N.V. BERNARDI REGISTERED CIVIL ENGINEER 9-30-08 45407	REVIEWED BY: PUBLIC WORKS DIRECTOR	DUBLIN BLVD / DOUGHERTY RD INTERSECTION IMPROVEMENT PROJECT DUBLIN BLVD AND DOUGHERTY RD TRAFFIC SIGNAL MODIFICATION	DRAWING No. E-2 SHEET 83 OF 92 SHEETS CONTRACT NO. 07-01
--	--	---------------------------------------	---	--

CONSTRUCTION NOTES (THIS SHEET ONLY)

- 1 REWIRE LOOP DETECTOR LEAD-IN CABLES IN THE CABINET SO THAT EACH DETECTOR IS WIRED TO ITS OWN CHANNEL. PROVIDE DIAGRAM SHOWING HOW CABLES ARE LANDED IN THE CABINET. LABEL EACH WIRE WITH PHASE AND DETECTOR NUMBER.
- 2 DISCONNECT TWO EXISTING BACK LOOPS AT CLOSEST PULL BOX. ABANDON LOOP WIRE IN PLACE.


DRAWINGS MAY NOT INCLUDE ALL RECENT UPDATES. FIELD VERIFICATION IS RECOMMENDED.

SEE DRAWING GN-01 FOR TRAFFIC SIGNAL GENERAL NOTES



Kimley»Horn

© 2017 KIMLEY-HORN AND ASSOCIATES, INC.
 4637 CHABOT DR, SUITE 300, PLEASANTON, CA 94588
 PHONE: 925-398-4840
 WWW.KIMLEY-HORN.COM




JANUARY 2017

ISSUES/REVISIONS

NO.	DATE	DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT



DRAWN BY: NAP/BUS/MP	DESIGNED BY: NAP/BUS/MP	CHECKED BY: BES	APPROVED BY:
PROJECT NUMBER: 097026201		SCALE: SEE PLAN	

TRAFFIC SIGNAL PLAN
 DUBLIN BLVD &
 SCARLETT DR


TS-11

FILE INFO: K:\BAY_IPTO_097026201 - MTC - Dublin Field Elements - NAP\CAD\Plansheets\TS-11 Dublin & Scarlett.dwg B:\nikito.petrov




CA: 1-800-227-2600
 CALL TWO WORKING DAYS BEFORE YOU DIG

CONTRACTOR:
 INSPECTOR:
 DATE COMPLETED: 1-21-04
 SCALE: 1"=20'



DESIGNED BY:	DRAWN BY:	CHECKED BY:
ESB	RC	ESB
PLANS PREPARED UNDER SUPERVISION OF		
Chris R. Kowal		
REGISTERED CIVIL ENGINEER		
1-17-04		
DATE:		RCE NO:



CITY OF DUBLIN
 PUBLIC WORKS DEPARTMENT
 City Offices, 100 Civic Plaza, Dublin, California 94008
 Public Works Department - Designing. 2023 683-8830

REVIEWED BY:	DATE:
[Signature]	
PUBLIC WORKS DIRECTOR/CITY ENGINEER	

TRAFFIC SIGNAL UPGRADE	DRAWING No. TS-2
SCARLETT DRIVE AT DUBLIN BOULEVARD	SHEET 2 of 7 SHEETS
	CONTRACT NO. 04-02


AS-BUILT DATED 1-28-2004. SEE NOTE 11 UNDER TRAFFIC SIGNAL GENERAL NOTES ON GN-01.

CONSTRUCTION NOTES (THIS SHEET ONLY)

- 1 DISCONNECT TWO EXISTING BACK LOOPS AT CLOSEST PULL BOX. ABANDON LOOP WIRE IN PLACE.
- 2 REWIRE LOOP DETECTOR LEAD-IN CABLES IN THE CABINET SO THAT EACH DETECTOR IS WIRED TO ITS OWN CHANNEL. PROVIDE DIAGRAM SHOWING HOW CABLES ARE LANDED IN THE CABINET. LABEL EACH WIRE WITH PHASE AND DETECTOR NUMBER.

DRAWINGS MAY NOT INCLUDE ALL RECENT UPDATES. FIELD VERIFICATION IS RECOMMENDED.

SEE DRAWING GN-01 FOR TRAFFIC SIGNAL GENERAL NOTES





JANUARY 2017

ISSUES/REVISIONS

NO.	DATE	DESCRIPTION

NO. DATE DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT



CITY OF DUBLIN PUBLIC WORKS
 REVIEW OF PLANS DOES NOT RELIEVE THE OWNER/DEVELOPER OF RESPONSIBILITY FOR CORRECTION OF MISTAKES, ERRORS OR OMISSIONS. FINAL APPROVAL OF CONSTRUCTION OR INSTALLATION SUBJECT TO INSPECTION, TEST, AND ACCEPTANCE.

APPROVED: _____ DATE: _____
 REVIEWED BY: APR 21 2016
 DUBLIN CITY ENGINEER

CITY OF DUBLIN
DUBLIN BLVD AT DEMARCUS BLVD
TRAFFIC SIGNAL MODIFICATION

TJKM
 4305 Hacienda Drive, Suite 650
 Pleasanton, CA 94588
 tjkm@tjkm.com

 DESIGNED: ESB
 DRAWN: RP
 CHECKED: ESB

DRAWING NO. **157-241-TS** SHEET **TS-1** OF _____
 DATE: 3/17/16 SCALE: 1"=20' PROJECT NO. 157-241

AS-BUILT DATED 3-17-2016. SEE NOTE 11 UNDER TRAFFIC SIGNAL GENERAL NOTES ON GN-01.



TRAFFIC SIGNAL PLAN DUBLIN BLVD & DEMARCUS BLVD


TS-12

CONSTRUCTION NOTES (THIS SHEET ONLY)

- 1 DISCONNECT TWO EXISTING BACK LOOPS AT CLOSEST PULL BOX. ABANDON LOOP WIRE IN PLACE.
- 2 REWIRE LOOP DETECTOR LEAD-IN CABLES IN THE CABINET SO THAT EACH DETECTOR IS WIRED TO ITS OWN CHANNEL. PROVIDE DIAGRAM SHOWING HOW CABLES ARE LANDED IN THE CABINET. LABEL EACH WIRE WITH PHASE AND DETECTOR NUMBER.

DRAWINGS MAY NOT INCLUDE ALL RECENT UPDATES. FIELD VERIFICATION IS RECOMMENDED.

SEE DRAWING GN-01 FOR TRAFFIC SIGNAL GENERAL NOTES



AS-BUILT DATED 2-12-2008. SEE NOTE 11 UNDER TRAFFIC SIGNAL GENERAL NOTES ON GN-01.



JANUARY 2017

ISSUES/REVISIONS

NO. DATE DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT



DRAWN BY: DESIGNED BY: CHECKED BY: APPROVED BY:

NAP/BUS/MP NAP/BUS/MP BES

PROJECT NUMBER: 097026201

SCALE: SEE PLAN

TRAFFIC SIGNAL PLAN DUBLIN BLVD & IRON HORSE PKWY

TS-13

17 OF 26





FILE INFO: K:\BAY_IPTO\097026201 - MTC - Dublin Field Elements - NAP\CAD\Plansheets\TS-13 Dublin & IronHorse.dwg BY: nikitto.petrov

CONSTRUCTION NOTES (THIS SHEET ONLY)



- 1 INSTALL OWNER-FURNISHED INTERSECTOR BICYCLE/VEHICLE MICROWAVE DETECTOR ON SIGNAL MAST ARM PER MANUFACTURER'S SPECIFICATIONS. CONTRACTOR TO COORDINATE WITH THE ENGINEER AND WESTERN PACIFIC SIGNAL REPRESENTATIVE FOR MICROWAVE DETECTION ZONES.
- 2 INSTALL OWNER-FURNISHED TCPI-4 INTERSECTOR POWER INJECTOR AND FOUR (4) TCIB INTERFACE BOARDS FOR INTERSECTOR DETECTORS IN EXISTING CABINET. FURNISH AND INSTALL ETHERNET PATCH CABLES BETWEEN THE POWER INJECTOR AND INTERFACE BOARDS.
- 3 FURNISH AND INSTALL PPB COMMON TO EACH PEDESTRIAN PHASE AS SHOWN BY THE CONDUCTOR SCHEDULE. COIL AT LEAST 20 FEET OF WIRE IN PULL BOX NEXT TO SIGNAL POLE WITH PUSH BUTTON. LABEL EACH WIRE WITH PHASE NUMBER.
- 4 DISCONNECT TWO EXISTING BACK LOOPS AT CLOSEST PULL BOX. ABANDON LOOP WIRE IN PLACE.
- 5 FURNISH AND INSTALL TRANSIT SIGNAL HEAD, "BUS SIGNAL" SIGN, R3-7 SIGN, "BUS EXEMPT" SIGN, AND 5-SECTION TRAFFIC SIGNAL HEAD ON EXISTING POLE PER DETAIL 'L' ON DRAWING DT-02.
- 6 FURNISH AND INSTALL 5-SECTION TRAFFIC SIGNAL HEAD. SEE DETAIL 'A' ON DRAWING DT-01.
- 7 FURNISH AND INSTALL LED R3-1 "NO RIGHT TURN" BLANK-OUT SIGN PER DETAIL 'N' ON DRAWING DT-02. WIRE THE SIGN WITH BUS PHASE. SIGN TO BE ACTIVE DURING THAT PHASE ONLY.
- 8 FURNISH AND INSTALL LED R3-1 "NO RIGHT TURN" BLANK-OUT SIGN PER DETAIL 'J' ON DRAWING DT-02. WIRE THE SIGN WITH BUS PHASE. SIGN TO BE ACTIVE DURING THAT PHASE ONLY.
- 9 FURNISH AND INSTALL ONE ETHERNET EXTENDER INSIDE THE SIGNAL POLE HANDHOLE, TO EXTEND ETHERNET CABLE TO INTERSECTOR DETECTOR LOCATED ON POLE (A).
- 10 FURNISH AND INSTALL ONE ETHERNET EXTENDER INSIDE THE SIGNAL POLE HANDHOLE, TO EXTEND ETHERNET CABLE TO INTERSECTOR DETECTOR LOCATED ON POLE (D).

SEE DRAWING GN-01 FOR TRAFFIC SIGNAL GENERAL NOTES



PROPOSED RING-BARRIER DIAGRAM

RING 1	01	09	02	03	04
RING 2	05	06	07	08	




JANUARY 2017

ISSUES/REVISIONS

NO.	DATE	DESCRIPTION
-----	------	-------------

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT



DRAWN BY:	DESIGNED BY:	CHECKED BY:	APPROVED BY:
NAP/BUS/MP	NAP/BUS/MP	BES	

PROJECT NUMBER: 097026201
 SCALE: SEE PLAN

TRAFFIC SIGNAL MODIFICATION DUBLIN BLVD & ARNOLD RD

TS-14

FILE INFO: K:\BAY_TPTO\097026201 - MTC - Dublin Field Elements - NAP\CAD\Plansheets\TS-14 Dublin & Arnold.dwg BY: niktia.petrov



CONDUCTOR SCHEDULE

AWG OR CABLE	NUMBER OF CONDUCTORS													
	RUN NUMBER													
	1	2	3	4	5	6	7	8	9	10	11	12	13	
NO. 14	Ø1	3	3					3	3	3				
	Ø2	6	6	3				3	3	3				3
	Ø3	6	6	3			3	3	3	3	3			
	Ø4	3	3					3	3	3	3			
	Ø5	3	3	3			3							3
	Ø6	6	6	3			3		3	3	3			
	Ø7	6	6						3					
	Ø8	3	3				3	3						
	Ø9	6	6	4				2	2					4
	Ø2P	4	4	2				2	2					2
	Ø4P	2	2					2	2	2	2			
	Ø6P	4	4				2	2	2	2				
	Ø8P	2	2				2	2						
	Ø2PPB	2	2					1						1
	Ø4PPB	2	2					2	2	1		1		
	Ø6PPB	2	2					1	1	1				
Ø8PPB	2	2	2	1	1									
Ø2 PPB COMMON	2	2					1					1		
Ø4 PPB COMMON	2	2					2	2	1		1			
Ø6 PPB COMMON	2	2	1			1	1	1	1			1		
Ø8 PPB COMMON	2	2	2	1	1	1	1	1	1					
PPB COMMON	2	2	2	1	1	1	1	1	1		1	1		
BLANK-OUT SIGN	2	2	2			2	2							
SPARES	6	6	3			3	3	3	3	3			3	
TOTAL NO. 14	16/63	16/63	9/22	3	4/22	3/13	6/32	5/27	2/24	11	2/4	2	4/11	
NO. 10	IISNS	4	4	2			2	2	2	2			2	
NO. 8	LIGHTING	4	4	2			2	2	2	2			2	
	SIGNAL NEUTRAL	2	2	1			1	1	1	1	1		1	
	TOTAL NO. 8	6	6	3			3	3	3	3	3	1	3	
DETECTOR LEAD-IN CABLE	Ø1	2	2	2	2									
	Ø2	8	8					8	8			1		
	Ø3	2	2					2		2	2		2	
	Ø4	2	2					2	2	2	2			
	Ø5	1	1					1	1			1		
	Ø6	8	8	8	1	7								
	Ø7	1	1					1	1	1	1			
	Ø8	3												
	SAMPLER LOOPS (S1, S2, S3)	3	3					3	3			3		
SAMPLER LOOPS (S4)	1	1	1			1	1							
SAMPLER LOOPS (S5, S6, S7)	3	3	3	3										
SAMPLER LOOPS (S8, S9)	2	2										2		
TOTAL DLC	36	33	14	6	8	1	19	15	3	3	5	4		
EMERGENCY VEHICLE PREEMPTION	EVA	1	1	1									1	
	EVB	1	1					1						
	EVC	1	1					1	1	1				
	EVD	1	1	1			1	1						
TOTAL EVP CABLE	4	4	2			1	1	2	1	1		1		
MICROWAVE DETECTION CABLE (CAT 5E)	Ø2 & Ø5	1	1	1									1	
	Ø4 & Ø7	1	1					1						
	Ø3 & Ø8	1	1	1			1	1						
	Ø1 & Ø6	1	1					1	1	1	1			
	TOTAL CAT 5E CABLE	4	4	2			1	1	2	1	1		1	
COHU CABLE	POWER/COAX/DATA	1	1					1	1	1				
	CONDUIT FILL (%)	19%	18%	27%	13%	19%	23%	25%	27%	16%	16%	13%	9%	21%
	CONDUIT SIZE (IN)	2-4"	2-4"	3"	2"	3"	2"	3 1/2"	3"	3"	2"	2"	2"	2"

ALL CONDUITS, CABLES, AND CONDUCTORS ARE EXISTING UNLESS OTHERWISE NOTED.

- = NEW CABLE OR CONDUCTOR
- △ = EXISTING CONDUIT RUN



EQUIPMENT SCHEDULE


LOCATION	STANDARD			LED LUMINAIRE	VEHICLE SIGNAL MOUNTING		PEDESTRIAN SIGNAL		PUSH BUTTON			IISNS LEGEND	SPECIAL NOTES
	TYPE	SIGNAL MAST ARM	LUMINAIRE MAST ARM		MAST ARM	POLE	MOUNT	POLE QUAD	Ø	ARROW	POLE QUAD		
(A)	61-5-80	65'	15'	104	3 MAS	SV-1-T	SP-1-T	W N E	-	-	-	Arnold Rd	INSTALL INTERSECTOR DETECTOR
(B)	PEDESTRIAN PUSH BUTTON POST	-	-	-	-	-	-	-	4	←	W N E	-	
(C)	1-B	-	-	-	-	TV-2-T	SP-1-T	W N E	6	→	W N E	-	
(D)	26-4-70	45'	15'	104	2 MAS	SV-1-T SV-1 N	SP-1-T	W N E	6	←	W N E	Dublin Blvd	FURNISH AND INSTALL BLANK OUT SIGN INSTALL INTERSECTOR DETECTOR
(E)	1-B	-	-	-	-	TV-2-T	SP-1-T	W N E	8	→	W N E	-	
(F)	61-5-80	60'	15'	104	3 MAS	SV-1-T SV-1-T N	SP-1-T	W N E	-	-	-	Arnold Rd	INSTALL INTERSECTOR DETECTOR
(G)	PEDESTRIAN PUSH BUTTON POST	-	-	-	-	-	-	-	8	←	W N E	-	
(H)	1-B	-	-	-	-	TV-2-T SV-1 N	SP-1-T	W N E	2	→	W N E	-	FURNISH AND INSTALL BLANK OUT SIGN
(I)	PEDESTRIAN PUSH BUTTON POST	-	-	-	-	-	-	-	2	↔	W N E	-	
(J)	24-4-70	45'	-	-	2 MAS	SV-1-T	SP-1-T	W N E	-	-	-	Dublin Blvd	INSTALL INTERSECTOR DETECTOR
(K)	PEDESTRIAN PUSH BUTTON POST	-	-	-	-	-	-	-	2	←	W N E	-	
(L)	1-B	-	-	-	-	TV-2-T	SP-1-T	W N E	4	→	W N E	-	
(M)	PEDESTRIAN PUSH BUTTON POST	-	-	-	-	-	-	-	4	↔	W N E	-	

ALL POLES AND EQUIPMENT ARE EXISTING UNLESS OTHERWISE NOTED.

N - NEW EQUIPMENT

OTHER REQUIREMENTS ARE COVERED BY NOTES, LEGEND, SPECIAL PROVISIONS AND CALTRANS STANDARD SPECIFICATIONS. FOR TYPE OF STANDARD, VEHICLE AND PEDESTRIAN MOUNTING, SEE CALTRANS STANDARD PLANS.

FOR THE PURPOSE OF LOCATING NEW AND EXISTING EQUIPMENT ON POLES, DUBLIN BOULEVARD SHALL BE CONSIDERED AN EAST-WEST ROADWAY.



EXISTING SIGNAL EQUIPMENT

SCALE 1"=40'



JANUARY 2017

ISSUES/REVISIONS

NO.	DATE	DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT

DESIGNED BY: NAP/BUS/MP
 CHECKED BY: BES
 PROJECT NUMBER: 097026201
 SCALE: SEE PLAN

TRAFFIC SIGNAL SCHEDULES DUBLIN BLVD & ARNOLD RD

TS-15

CONSTRUCTION NOTES (THIS SHEET ONLY)

- 1 DISCONNECT TWO EXISTING BACK LOOPS AT CLOSEST PULL BOX. ABANDON LOOP WIRE IN PLACE.

SEE DRAWING GN-01 FOR TRAFFIC SIGNAL GENERAL NOTES

DRAWINGS MAY NOT INCLUDE ALL RECENT UPDATES. FIELD VERIFICATION IS RECOMMENDED.

Kimley-Horn

© 2017 KIMLEY-HORN AND ASSOCIATES, INC.
4637 CHABOT DR, SUITE 300, PLEASANTON, CA 94588
PHONE: 925-398-4840
WWW.KIMLEY-HORN.COM




JANUARY 2017

ISSUES/REVISIONS

NO. DATE DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT

NORTH




SCALE: SEE PLAN

TRAFFIC SIGNAL PLAN DUBLIN BLVD & PERSIMMON PL - SYBASE DR

TS-16

20 OF 26



GENERAL NOTES (SHEETS E1-E4)

ALL MATERIALS AND WORKMANSHIP SHALL FULLY CONFORM WITH THE LATEST EDITIONS OF THE NATIONAL ELECTRICAL CODE, STD. STANDARD PLANS AND SPECIFICATIONS, CALIFORNIA MISC. AND STANDARD, AND THE CITY OF DUBLIN TRAFFIC SIGNAL AND ROADWAY LIGHTING SPECIFICATIONS AND DETAILS. WHERE THERE IS CONFLICT, THE MORE RESTRICTIVE SHALL APPLY.

2. CONTRACTOR TO FIELD VERIFY THE EXACT LOCATION OF EXISTING ELECTRICAL EQUIPMENT.

3. LOCATIONS OF STANDARDS, PULL BOXES, CABINETS, AND OTHER EQUIPMENT SHOWN ON THE PLANS ARE APPROXIMATE AND SHALL BE LOCATED IN THE FIELD BY THE ENGINEER. POLE LOCATIONS SHALL BE DETERMINED AND CHECKED FOR UTILITY CONFLICTS PRIOR TO DRILLING FOUNDATIONS.

4. THIS PLAN IS SCHEMATIC IN NATURE AND IT IS ACCURATE FOR ELECTRICAL WORK ONLY. THE CONTRACTOR IS RESPONSIBLE FOR CONSTRUCTING A COMPLETE AND FUNCTIONAL TRAFFIC SIGNAL ACCORDING TO CITY OF DUBLIN SPECIFICATIONS AND PERCEIVED ANOMALIES SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER IN A TIMELY MANNER.

5. THE CONTRACTOR SHALL NOTIFY UNDERGROUND SERVICE ALERT A MINIMUM OF FORTY EIGHT (48) HOURS PRIOR TO ANY EXCAVATION. THE CONTRACTOR IS RESPONSIBLE FOR COMPLYING WITH ALL REQUIRED CLEARANCES FROM OVERHEAD AND UNDERGROUND UTILITIES.

6. SEE STATE STANDARD PLANS ES-1A, ES-1B, AND ES-1C FOR LEGEND, SYMBOLS AND ABBREVIATIONS.

7. PEDESTRIAN PUSH BUTTON SIGN SHALL BE R10-36.

8. CONDUIT AND FITTINGS: ALL CONDUIT AND FITTINGS SHALL BE UL APPROVED. USE MINIMUM 2" SCHEDULE 40 PVC CONDUIT AND FITTINGS. THE MINIMUM RADIUS OF BEND SHALL BE 18 INCHES. ALL BENDS AND JOINTS SHALL BE ACCOMPLISHED WITH FACTORY FORMED SECTIONS. ALL EMPTY CONDUIT ENDS SHALL BE PLUGGED. ALL OTHER CONDUIT SHALL HAVE BELL ENDS AND SHALL BE SEALED WITH GULF SEAL. USE UNDERGROUND CONDUIT AND ALL METAL PARTS SHALL BE CONTINUOUSLY BONDED AND GROUNDING. PROVIDE A 1/2" PULL WIRE IN ALL EMPTY CONDUITS. ALL CROSSINGS SHALL BE PERPENDICULAR TO THE STREET. SIGNAL INTERCONNECT CONDUIT SHALL COMPLY WITH THE SPECIAL PROVISIONS AND SHALL BE KEPT SEPARATE FROM OTHER CONDUITS. MINIMUM RADIUS FOR INTERCONNECT CONDUIT BENDS SHALL BE 3'.

9. CONDUIT DEPTH: CONDUIT SHALL BE INSTALLED AT A MINIMUM DEPTH OF 24" BELOW SIDEWALK OR FLANKER STRIPS AND 36" BELOW ROADWAYS. REFER TO THE SPECIFICATION FOR ADDITIONAL INFORMATION REGARDING SPECIAL LOCATIONS.

10. WIRE: REFER TO THE CITY OF DUBLIN TRAFFIC SIGNAL SPECIFICATION. NO MECHANICAL DEANS SHALL BE USED TO PULL WIRE.

11. PULL BOXES: PULL BOXES SHALL CONFORM TO STATE STANDARD DRAWING ES-8A. BOXES SHALL BE CONSTRUCTED WITH A MINIMUM DEPTH OF EIGHT (8) INCHES AND A MINIMUM OF SIX (6) INCHES IN WIDTH OUTSIDE OF THE PULL BOX ON ALL SIDES. DRAIN ROCK SHALL BE 1-1/2" PLAT SMOOTH RIVER DRAIN ROCK WHICH IS CLEAR AND FREE OF LINT AND DEBRIS. THE COVERS SHALL HAVE BRASS HOLDOWN LINES AND SHALL BE GROUNDING WITH APPROPRIATE IDENTIFICATION. PULL BOXES SHALL NOT BE MORE THAN 100 FEET APART. ON LONG RUNS, EXCEPT THAT SIX PULL BOXES MAY BE 200 FEET APART. WHERE PULL BOXES ARE SUBJECT TO TRAFFIC LOADS, THEY SHALL BE SET ON A CONCRETE FOOTING AND THE COVER SHALL BE CAST ON TOP. STEEL OF SUFFICIENT STRENGTH TO WITHSTAND THE TRAFFIC LOAD. MINIMUM PULL BOX SIZE SHALL BE #5, EXCEPT TWO PULL BOXES WHICH SHALL BE #8 WITH "INTERCONNECT" LABELED LIDS.

12. SPLICING: ALL SPLICES SHALL BE MADE IN PULL BOXES ONLY. SPLICES SHALL BE MADE WITH "C" TYPE COMPRESSION FITTINGS AND INSULATED BY METHOD B AS SHOWN IN STATE STANDARD PLAN ES-13.

13. SIGNAL HEADS: ALL SIGNAL HEADS SHALL BE 12" AND SHALL HAVE BACKLITES. SIGNAL HEAD BACK PLATES SHALL BE SOLID METAL TYPE.

14. LED SIGNAL: ALL VEHICLE AND PEDESTRIAN SIGNALS SHALL BE LED AND SHALL CONFORM TO THE CITY OF DUBLIN TRAFFIC SIGNAL AND ROADWAY LIGHTING SPECIFICATIONS. THE CONTRACTOR SHALL PROVIDE 3% SPARE LED MODULES WITH A MINIMUM OF ONE OF EACH TYPE (12" RED BALL, 12" RED ARROW, 12" YELLOW BALL, 12" YELLOW ARROW, 12" GREEN BALL, 12" GREEN ARROW, AND PEDESTRIAN COUNTDOWN HEAD).

15. DETECTORS: LOOP DETECTORS SHALL BE CENTERED IN EFFECTIVE LANE UNLESS OTHERWISE DIRECTED BY THE ENGINEER. POINT DETECTOR LOOPS SHALL BE MONIRED TYPE E LOOPS THAT DETECT PEDESTRIANS AND SHALL BE INSTALLED 1' BEHIND THE LIMIT LINE.

16. LED SIGNS: MORNING AND SPELLING OF STREET NAMES SHALL BE APPROVED BY THE CITY PRIOR TO ORDERING LED SIGN EQUIPMENT.

17. SEE SHEET E2 FOR THE REMOVAL OF EXISTING SIGNAL EQUIPMENT.

18. ALL CAMERA AND SENSOR CABLES ARE TO BE INSTALLED INSIDE OF MAST ARMS AND POLES.

PROJECT NOTES (SHEETS E1-E2)

1 EXISTING TYPE 2070 "36" CONTROLLER ASSEMBLY AND CABINET TO REMAIN. FURNISH AND INSTALL NEW BATTERY BACKUP SYSTEM.

2 EXISTING TYPE 1-0 SERVICE EQUIPMENT ENCLOSURE TO REMAIN. REELIN 3/4" THROUGH NEW PULL BOX OUTSIDE OF RAMP AND RECONNECT.

3 FURNISH AND INSTALL COLOR IP-CAMERA ON TOP OF POLE. FURNISH CONTROLLER SYSTEM COMMUNICATIONS EQUIPMENT PER CITY SPECIFICATIONS.

4 POT HOLE TO VERIFY LOCATION OF EXISTING UNDERGROUND UTILITIES.

5 EXISTING 0-3"Ø, 1 INT, 1 ØC, REMOVE EXISTING 1Ø, INSTALL 1 FO (48 STRAND) TO SIGNAL CONTROLLER AT DUBLIN/AIRWOLD.

6 EXISTING 2-3"Ø, 1 INT, 1 ØC, REMOVE EXISTING 1Ø, INSTALL 1 FO (48 STRAND) TO SIGNAL CONTROLLER AT SYBASE/HADESKVA.

7 EXISTING 3"Ø, 1 INT, 1 ØC, REMOVE EXISTING 1Ø, INSTALL 2 FO.

8 FURNISH AND INSTALL MOTION AND PRESENCE SENSOR ON MAST ARM PER CITY SPECIFICATIONS.

9 FURNISH AND INSTALL 3-SECTION SIGNAL HEAD AS SHOWN IN DETAIL B, SEE THIS SHEET.

10 1-3"Ø, 1 INT, 1 ØC, 1 FO (48 STRAND).



APPROVED FOR ELECTRICAL WORK ONLY

AS-BUILT DATED 11-18-2014. SEE NOTE 11 UNDER TRAFFIC SIGNAL GENERAL NOTES ON GN-01.

Deleted pole M+N
Ø6-1, Ø6-2, Ø6-3 uses
conduit



SCALE: 1" = 20'
DATE: 11-18-14
DESIGNED BY: NAP/BUS/MP
CHECKED BY: BES
PROJECT NUMBER: 097026201
SCALE: SEE PLAN
SHEET NO: E1
TOTAL SHEETS: 23 OF 26

FILE INFO: K:\BAY_TPTO\097026201 - MTC - Dublin Field Elements - NAP\CAD\Plansheets\TS-16 Dublin & Persimmon.dwg




CONSTRUCTION NOTES (THIS SHEET ONLY)

- 1** DISCONNECT TWO EXISTING BACK LOOPS AT CLOSEST PULL BOX. ABANDON LOOP WIRE IN PLACE.
- 2** DISCONNECT EXISTING COUNT LOOPS AT THE CONTROLLER CABINET AND ABANDON IN PLACE.
- 3** REWIRE LOOP DETECTOR LEAD-IN CABLES IN THE CABINET SO THAT EACH DETECTOR IS WIRED TO ITS OWN CHANNEL. PROVIDE DIAGRAM SHOWING HOW CABLES ARE LANDED IN THE CABINET. LABEL EACH WIRE WITH PHASE AND DETECTOR NUMBER.

DRAWINGS MAY NOT INCLUDE ALL RECENT UPDATES. FIELD VERIFICATION IS RECOMMENDED.

SEE DRAWING GN-01 FOR TRAFFIC SIGNAL GENERAL NOTES



PROJECT NOTES:

- 1** EXISTING TRAFFIC SIGNAL TSP-390 CONTROLLER IN TYPE "N" CABINET WITH TYPE II SERVICE ATTACHED. INSTALL NEW DETECTOR COMPLETE WIRING, AND MODIFY CONTROL PROGRAM AND DATABASE AS REQUIRED FOR THE OPERATION.
- 2** RELOCATE EXISTING 1-B POLE AND EQUIPMENT TO NEW LOCATION, AS SHOWN. **FA** EXISTING FOUNDATION.
- 3** EXISTING 115V 1-PHASE ALL EQUIPMENT TO BE RELOCATED, AS SHOWN. **FA** EXISTING FOUNDATION.

GENERAL NOTES:

1. ALL WORK ON THESE PLANS SHALL CONFORM TO THE JULY 1992 EDITION OF THE STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION (CALTRANS) STANDARD SPECIFICATIONS, STANDARD PLANS, SIGN SPECIFICATIONS SHEETS, TRAFFIC MANUAL, AND THE SPECIAL PROVISIONS.
2. LOCATION OF SPANNS, PULL BOXES AND OTHER EQUIPMENT SHOWN ON THIS PLAN ARE APPROXIMATE AND SHALL BE LOCATED IN THE FIELD BY THE ENGINEER.
3. CONTRACTOR SHALL TAKE CARE IN LOCATING DETECTOR LOOPS NEAR MANHOLES, WATER VALVES, IRREGULARLY PLACED CURBS SHALL BE LOCATED MINIMUM OF 24 INCHES FROM THESE OBJECTS. THE LOCATION OF THE OBJECTS IN THE VICINITY OF THESE OBJECTS SHALL BE DETERMINED BY THE ENGINEER.
4. THIS PLAN ACCURATE FOR ELECTRICAL WORK.
5. ALL PULL BOXES SHALL BE NDS EXCEPT NOTED.
6. ALL SIGNAL HEADS SHALL BE 12" TYPE. SIGNALS SHALL HAVE BACKLIGHTING.
7. ALL NEW RED LEVELS AND RED BIRD PEDESTRIAN INDICATORS SHALL BE LED TYPE. CONTRACTOR TO PROVIDE RED SPARE LED INDICATORS (MINIMUM ONE OF EACH TYPE).
8. CONTRACTOR SHALL VERIFY OVERHEAD AND UNDERGROUND CLEARANCE WITH CALIF. PACIFIC BELL AND OTHER AFFECTED UTILITIES PRIOR TO THE START OF WORK.
9. CONTRACTOR SHALL VERIFY WORKING AND SPELLING OF STREET NAMES PRIOR TO STARTING FIELD EQUIPMENT.
10. ALL DETECTORS SHALL BE SINGLE CHANNEL.

RECORD DRAWINGS
 THESE ARE THE FINAL CONSTRUCTION PLANS FOR THE PROJECT WITH THE APPROVE NOTED FOR FIELD CHANGES BROUGHT TO THE ATTENTION OF THE ENGINEER BY THE DEVELOPER, CONTRACTOR & THE AGENT.

Chris D. Boud
 CIVIL ENGINEER
 SEP. 21 2017
 EXP. 9/21/22

BEFORE EXCAVATING
 CALL U.S.A.
 UNDERGROUND SERVICE ALERT
 800-227-2600
 TWO WORKING DAYS BEFORE ALL
 PLANNED WORK OPERATIONS

<p>CONSTRUCTION RECORD</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>CONTRACTOR</td><td></td></tr> <tr><td>INSPECTOR</td><td></td></tr> <tr><td>DATE COMPLETED</td><td>3-12-02</td></tr> </table> <p>SCALE: 1"=20'</p>	CONTRACTOR		INSPECTOR		DATE COMPLETED	3-12-02	<p>DESIGNED BY: ESB DRAWN BY: ESB CHECKED BY: JW</p> <p>PLANS PREPARED UNDER SUPERVISION OF</p> <p>REGISTERED CIVIL ENGINEER</p> <p>DATE: _____ RC# NO. _____</p>	<p>REVIEW BY: <i>[Signature]</i> PUBLIC WORKS DIRECTOR/CITY ENGINEER</p> <p>DATE: _____</p>	<p>CITY OF DUBLIN PUBLIC WORKS DEPARTMENT DUBLIN BOULEVARD AT HACIENDA DRIVE TRAFFIC SIGNAL MODIFICATION</p> <p>DRAWING No. <i>XX-XX-X</i> SHEET <i>XX</i> of <i>XX</i> JOB No. 157-123</p>
CONTRACTOR									
INSPECTOR									
DATE COMPLETED	3-12-02								

AS-BUILT DATED 12-16-2002. SEE NOTE 11 UNDER TRAFFIC SIGNAL GENERAL NOTES ON GN-01.



Kimley Horn
 © 2017 KIMLEY-HORN AND ASSOCIATES, INC.
 4637 CHABOT DR., SUITE 300, PLEASANTON, CA 94588
 PHONE: 925-398-4840
 WWW.KIMLEY-HORN.COM




JANUARY 2017

ISSUES/REVISIONS

NO.	DATE	DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT



DRAWN BY: NAP/BUS/MP	DESIGNED BY: NAP/BUS/MP	CHECKED BY: BES	APPROVED BY:
PROJECT NUMBER: 097026201			SCALE: SEE PLAN

**TRAFFIC SIGNAL PLAN
 DUBLIN BLVD &
 HACIENDA DR**

TS-17

FILE INFO: K:\BAY_IPTO\097026201 - MTC - Dublin Field Elements - NAP\CAD\Drawings\17 Dublin & Hacienda.dwg BY: mikto.petrov

CONSTRUCTION NOTES (THIS SHEET ONLY)

1 DISCONNECT TWO EXISTING BACK LOOPS AT CLOSEST PULL BOX. ABANDON LOOP WIRE IN PLACE.

SEE DRAWING GN-01 FOR TRAFFIC SIGNAL GENERAL NOTES

DRAWINGS MAY NOT INCLUDE ALL RECENT UPDATES. FIELD VERIFICATION IS RECOMMENDED.

Kimley Horn

© 2017 KIMLEY-HORN AND ASSOCIATES, INC.
4637 CHABOT DR, SUITE 300, PLEASANTON, CA 94588
PHONE: 925-398-4840
WWW.KIMLEY-HORN.COM



JANUARY 2017

ISSUES/REVISIONS

RECORD DRAWINGS
These Record Drawings have been prepared based on information submitted by others, partially or totally. While this information is believed to be reliable, TJKM Transportation Consultants is not responsible for its accuracy, nor for errors or omissions which may have been incorporated into these documents as a result.

Chris D. Kinzel 15347 3-31-07
Chris D. Kinzel R.C.E. No. Exp. Date
Date: 2-20-07


BEFORE EXCAVATING
CALL U.S.A.
UNDERGROUND SERVICE ALERT
800-227-2600
TWO WORKING DAYS BEFORE ALL
PLANNED WORK OPERATIONS

CITY OF DUBLIN PUBLIC WORKS
REVIEW OF PLANS DOES NOT RELIEVE THE OWNER/DEVELOPER OF RESPONSIBILITY FOR CORRECTION OF MISTAKES, ERRORS OR OMISSIONS. FINAL APPROVAL OF CONSTRUCTION OR INSTALLATION SUBJECT TO INSPECTION, TEST, AND ACCEPTANCE.

REVIEWED BY: *Michael Peter* DATE: 4/4/05
DUBLIN PUBLIC WORKS DIRECTOR

CITY OF DUBLIN			
HACIENDA DRIVE AT MARTINELLI WAY			
TRAFFIC SIGNAL INSTALLATION			
DESIGNED: RC	DRAWING NO. 157-174	SHEET TS-8 OF 17	
DRAWN: RC	DATE: 11/8/05	SCALE: 1"=20'	PROJECT NO. 157-174
CHECKED: ESB			

Transportation Consultants
5960 Inglewood Drive, Suite 100
Pleasanton, CA 94588
Phone: (925) 463-0611 Fax: (925) 463-3690
email: tkm@tkm.com



AS-BUILT DATED 11-8-2005. SEE NOTE 11 UNDER TRAFFIC SIGNAL GENERAL NOTES ON GN-01.



FILE INFO: K:\BAY_IPTO\097026201 - MTC - Dublin Field Elements - NAP\CAD\Plansheets\TS-18 Hacienda & Martinelli.dwg BY: mtkto.petrov



TRAFFIC SIGNAL PLAN
HACIENDA DR & MARTINELLI WY

TS-18


22 OF 26

CONSTRUCTION NOTES (THIS SHEET ONLY)

- 1 FURNISH AND INSTALL TRANSIT SIGNAL HEAD AND "RAPID BUS SIGNAL" SIGN ON EXISTING POLE PER DETAIL 'L' ON DRAWING DT-02.
- 2 FURNISH AND INSTALL LED R3-1 "NO RIGHT TURN" BLANK OUT SIGN ON NEW 1-B POLE. SEE DETAIL 'N' ON DRAWING DT-01. WIRE THE SIGN WITH THE BUS PHASE. SIGN TO BE ACTIVE DURING THAT PHASE ONLY.
- 3 FURNISH AND INSTALL LED R3-1 "NO RIGHT TURN" BLANK OUT SIGN ON EXISTING POLE. SEE DETAIL 'J' ON SHEET DT-02. WIRE THE SIGN WITH BUS PHASE. SIGN TO BE ACTIVE DURING THAT PHASE ONLY.
- 4 FURNISH AND INSTALL TRANSIT SIGNAL HEAD AND "RAPID BUS SIGNAL" SIGN ON NEW POLE PER DETAIL 'R' ON DRAWING DT-02.
- 5 INSTALL PCC PAD FOR SIGNAL POLE AND PULL BOX PER DETAIL 'Q' ON DRAWING DT-01. ADJUST EXISTING PULL BOX TO GRADE. THE DIMENSIONS OF THE PAD SHALL BE DETERMINED IN THE FIELD BY THE ENGINEER.
- 6 REMOVE EXISTING POLE AND FOUNDATION. EXISTING POLE TO BE BECOME THE PROPERTY OF THE CONTRACTOR. FOUNDATION TO BE REMOVED IN ITS ENTIRETY. FURNISH AND INSTALL NEW CALTRANS STANDARD TYPE 15TS POLE AND FOUNDATION. RELOCATE ALL EXISTING SIGNAL EQUIPMENT TO NEW FRAMEWORK ON NEW POLE. MAINTAIN ROTATION AND WORKING STATE OF SIGNAL EQUIPMENT AS IT WAS ON EXISTING POLE.
- 7 REMOVE EXISTING POLE AND FOUNDATION. EXISTING POLE TO BE BECOME THE PROPERTY OF THE CONTRACTOR. FOUNDATION TO BE REMOVED IN ITS ENTIRETY. FURNISH AND INSTALL NEW CALTRANS STANDARD TYPE 1-B POLE AND FOUNDATION. RELOCATE ALL EXISTING SIGNAL EQUIPMENT TO NEW POLE. MAINTAIN ROTATION AND WORKING STATE OF EXISTING SIGNAL EQUIPMENT AS IT WAS ON EXISTING POLE.



EMERGENCY VEHICLE PREEMPTION
 evo = ø2 & ø5
 evb = ø4 & ø7
 evc = ø1 & ø6
 evd = ø3 & ø8




*ø9 ACTIVATED BY TSP AND LOOP DETECTORS
 *BLANK-OUT SIGN TO BE ACTIVE DURING THIS PHASE

EMERGENCY VEHICLE PREEMPTION
 evo = ø2 & ø5
 evb = ø4 & ø7
 evc = ø1 & ø6
 evd = ø3 & ø8

RING 1	ø1	ø9	ø2	BARRIER	ø3	ø4	BARRIER
RING 2	ø5	ø6			ø7	ø8	

RING-BARRIER DIAGRAM



TRAFFIC SIGNAL LEGEND: (THIS SHEET ONLY)

- PROPOSED SIGNAL
- EXISTING SIGNAL TO BE RELOCATED
- EXISTING SIGNAL TO REMAIN

SEE DRAWING GN-01 FOR TRAFFIC SIGNAL GENERAL NOTES




JANUARY 2017

ISSUES/REVISIONS

NO. DATE DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT



DRAWN BY: NAP/BUS/MP
 DESIGNED BY: NAP/BUS/MP
 CHECKED BY: BES
 APPROVED BY:
 PROJECT NUMBER: 097026201
 SCALE: SEE PLAN

TRAFFIC SIGNAL MODIFICATION DUBLIN BLVD & TASSAJARA RD

TS-19

FILE INFO: K:\BAY_IPTO\097026201 - MTC - Dublin Field Elements - NAP\CAD\Drawings\TS-0X TASSAJARA ROAD.dwg Bynikito.petrov



1

2

3

4

AWG OR CABLE		CONDUCTOR SCHEDULE															
		NUMBER OF CONDUCTORS															
		RUN NUMBER															
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
NO. 14	Ø1										6	6	6	3	3		
	Ø2					3		3	3	6	6	6	3				
	Ø3	3		3	3	3		3	3	6	6	6	3	3	3	3	
	Ø4									6	6	6	3	3	3	3	
	Ø5		3	3	3	6		6	6	6	6	6	3	3	3		
	Ø6		3	3	3	3		3	3	6	6	6	3	3	3		
	Ø7						3	3	3	6	6	6					
	Ø8	3		3	3	3	3	6	6	6	6						
	Ø9*					②	②	②	②	④	④	④					
	OLA					2	2	2	4	4	4	2					
	Ø2P					2	2	2	4	4	4	2					
	Ø4P								4	4	4	2	2	2			
	Ø6P		2	2	2	2		2	2	4	4	2	2	2			
	Ø8P	2		2	2	2		4	4	4	4						
	Ø2PPB						1	2	2	3	3						
	Ø4PPB							2	2	2	2	1	1	1			
	Ø6PPB	1		1	1	1		1	1	2	2	1	1	1	1	1	
	Ø8PPB							3	3	3	3						
	PPB COMMON	1	1	1	2	3		3	3	3	3	4	1	1	1	1	
	IISNS	2		2	2	2		2	2	4	4	2	2	2			
BLANK-OUT SIGN*	②	②	②	②	②	④	④	④	④	④							
SPARES	1	1	4	4	2	3	3	3	4	4	1	3	3	3	3		
TOTAL NO. 14		15	13	28	29	40	6/11	54	54	98	98	37	24	24	13	5	
NO. 8	LIGHTING (240V)	2		2	2	2		2	2	4	4	2	2	2			
	SIGNAL NEUTRAL	1	1	2	2	2	1	3	3	4	4	1	1	1	1	1	
	TOTAL NO. 8	3	1	4	4	4	1	1	5	5	8	8	3	3	1	1	
DETECTOR LEAD-IN CABLE	Ø1				3	3		3	3	3	3						
	Ø2									12	12	12					
	Ø3								6	6	6						
	Ø4									12	12	12	12	12	12	1	
	Ø5									4	4	4	4				
	Ø6	10		10	10	10		10	10	10	10						
	Ø7									1	1	1	1	1	1	1	
	Ø8																
	Ø9								12	12	12	12					
	TOTAL DLC	10		10	13	13		25	31	60	60	29	17	13	13	2	
CABLE	EVA					1		1	1	1	1						
	EVB									1	1						
	EVC									1	1	1	1	1	1		
	EVD	1		1	1	1		1	1	1	1						
TOTAL CABLES	1		1	1	2		2	2	4	4	1	1	1				
CONDUIT FILL (%)		17%	12%	19%	21%	25%	14%	39%	44%	23%	23%	37%	23%	20%	16%	5%	
CONDUIT SIZE (IN)		3"	2"	3"	3"	3"	2"	3"	3"	2-4"	2-4"	3"	3"	3"	3"	3"	

*CONTRACTOR TO VERIFY PRESENCE OF EXISTING SPARE CONDUCTORS. CONTRACTOR SHALL USE EXISTING SPARE CONDUCTORS FOR BUS SIGNAL PHASE AND BLANK-OUT SIGN.

ALL CONDUITS, CABLES, AND CONDUCTORS ARE EXISTING UNLESS OTHERWISE NOTED.

○ = NEW CABLE OR CONDUCTOR
 ◊ = EXISTING SPARE CABLE OR CONDUCTOR
 △ = EXISTING CONDUIT RUN
 ▲ = NEW CONDUIT RUN

ALL EXISTING CONDUITS TO BE USED OR REUSED MUST BE CLEANED WITH A MANDREL OR CYLINDRICAL WIRE BRUSH AND BLOWN OUT WITH COMPRESSED AIR. NO CONDUCTORS MUST BE PULLED INTO EXISTING CONDUIT UNTIL THE EXISTING CONDUIT IS CLEANED OUT.



EQUIPMENT SCHEDULE													
LOCATION	STANDARD			LED LUMINAIRE NUMBER	VEHICLE SIGNAL MOUNTING		PEDESTRIAN SIGNAL		PUSH BUTTON			IISNS LEGEND	SPECIAL NOTES
	TYPE	SIGNAL MAST ARM	LUMINAIRE MAST ARM		MAST ARM	POLE	MOUNT	POLE QUAD	Ø	ARROW	POLE QUAD		
(A)	SPECIAL	85'	15'	133	4 MAS	SV-1-T	-	-	-	-	-	-	Dublin Blvd
(B)	PPB	-	-	-	-	-	-	-	2	←	W N S E	-	
(C)	15TS ^N	-	15' ^N	133 ^N	-	SV-2-T ^N	SP-2-T ^N	W N R S E	4	→	W N S E	-	
(D)	SPECIAL	80'	15'	133	4 MAS	SV-1-T	SP-1-T	W N S E	4	←	W N S E	Tassajara Rd	
(E)	1-B	-	-	-	-	TV-2-T	SP-1-T	W N S E	2	→	W N S E	-	
(F)	SPECIAL	85'	15'	133	4 MAS	SV-1-T	SP-1-T	W N S E	8	-	-	Dublin Blvd	FURNISH AND INSTALL BLANK OUT SIGN
(G)	1-B	-	-	-	-	-	SP-1-T	W N S E	6	←	W N S E	-	
(H)	1-B	-	-	-	-	TV-1-T	-	-	8	→	W N S E	-	
(I)	SPECIAL	70'	15'	133	3 MAS	SV-1-T	SP-1-T	W N S E	2	←	W N S E	Tassajara Rd	
(J)	1-B	-	-	-	-	SV-1-T	SP-1-T	W N S E	-	-	-	-	
(K)	1-B ^N	-	-	-	-	TV-2-T ^R	SP-1-T ^R	W N S E	6	→	W N S E	-	FURNISH AND INSTALL BLANK OUT SIGN

ALL POLES AND EQUIPMENT ARE EXISTING UNLESS OTHERWISE NOTED.

N - NEW EQUIPMENT
 R - RELOCATED EQUIPMENT

OTHER REQUIREMENTS ARE COVERED BY NOTES, LEGEND, SPECIAL PROVISIONS AND CALTRANS STANDARD SPECIFICATIONS. FOR TYPE OF STANDARD, VEHICLE AND PEDESTRIAN MOUNTING, SEE CALTRANS STANDARD PLANS.

FOR THE PURPOSE OF LOCATING NEW AND EXISTING EQUIPMENT ON POLES, DUBLIN BOULEVARD SHALL BE CONSIDERED AN EAST-WEST ROADWAY.



JANUARY 2017

ISSUES/REVISIONS


NO.	DATE	DESCRIPTION
-----	------	-------------

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT

DESIGNED BY: NAP/BUS/MP
 CHECKED BY: BES
 PROJECT NUMBER: 097026201
 SCALE: SEE PLAN

TRAFFIC SIGNAL SCHEDULES DUBLIN BLVD & TASSAJARA RD

TS-20



STRIPING LEGEND (SS-01 & SS-02)

- PROPOSED MARKING PER CALTRANS STANDARD DETAILS
- EXISTING MARKING TO REMAIN
- EXISTING MARKING TO BE REMOVED
- PROPOSED STRIPING
- EXISTING STRIPING TO REMAIN
- EXISTING STRIPING TO BE REMOVED.
- CONFORM TO EXISTING STRIPING

STRIPING NOTES (THIS SHEET ONLY)

- (XX) INSTALL STRIPING DETAIL NUMBER "XX" PER CALTRANS STANDARD PLANS A20A, A20B, RSP A20C, A20D, AND RSP A24A.
- [1] INSTALL CALTRANS STANDARD PAVEMENT LEGEND (THERMOPLASTIC).

GENERAL NOTES: (SS-01 & SS-02)


- ALL SIGN CODES REFER TO THE 2014 CALIFORNIA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (CAMUTCD) UNLESS OTHERWISE NOTED.
- ALL STRIPING DETAILS, PAVEMENT MARKING SYMBOLS, AND LEGENDS MUST BE INSTALLED PER CALTRANS STANDARD PLANS.
- ALL EXISTING STRIPING AND PAVEMENT MARKINGS CONFLICTING WITH THE NEW STRIPING SHALL BE REMOVED.
- ALL EXISTING SIGNS TO REMAIN UNLESS OTHERWISE NOTED.



JANUARY 2017

ISSUES/REVISIONS		
NO.	DATE	DESCRIPTION


**DUBLIN BOULEVARD
 FIELD ELEMENTS
 CONSTRUCTION
 PROJECT**




DRAWN BY: NAP/BJS/MP	DESIGNED BY: NAP/BJS/MP	CHECKED BY: BES	APPROVED BY:
PROJECT NUMBER: 097026201		SCALE: SEE PLAN	

**SIGNING & STRIPING
 DUBLIN BLVD AT
 VILLAGE PKWY AND
 ARNOLD RD**

SS-01



FILE INFO: K:\BAY_IPTO\097026201 - MTC - Dublin Field Elements - NAP\CAD\Drawings\SS-01 Striping.dwg B:\mktia\petrov




JANUARY 2017

ISSUES/REVISIONS

NO.	DATE	DESCRIPTION

DUBLIN BOULEVARD FIELD ELEMENTS CONSTRUCTION PROJECT




DRAWN BY: NAP/BUS/MP	DESIGNED BY: NAP/BUS/MP	CHECKED BY: BES	APPROVED BY:
PROJECT NUMBER: 097026201		SCALE: SEE PLAN	

SIGNING & STRIPING DUBLIN BLVD & TASSAJARA RD

SS-02

- STRIPING NOTES (THIS SHEET ONLY)**
- ⊗ INSTALL STRIPING DETAIL NUMBER "XX" PER CALTRANS STANDARD PLANS A20A, A20B, RSP A20C, A20D, AND RSP A24A.
 - 1 INSTALL CALTRANS STANDARD PAVEMENT LEGEND (THERMOPLASTIC)

- SIGNING NOTES (THIS SHEET ONLY)**
- 1 FURNISH AND INSTALL ROADSIDE SIGN.
 - 2 FURNISH AND INSTALL NEW "BUS EXEMPT" SIGN UNDERNEATH EXISTING R15-7R SIGN. SEE DETAIL "E" FOR SIGN DIMENSIONS. MOVE EXISTING R8-3A SIGN DOWN AS APPROPRIATE ON THE POLE.



FILE INFO: K:\BAY_IPTO\097026201 - MTC - Dublin Field Elements - NAP\CAD\Plansheets\SS-02_Signing & Striping.dwg
 BY: miki.etrov
 C:\

